



シリンダー取付寸法

単位:mm

シリンダー能力	穴数	ネジ山サイズ	深さ	穴位置(センター)
4.5	2†	1/4-20	9.5	25.4
10		5/16-18	12.7	39.7
14		3/8-16		47.6
23		1/2-13	58.7	
50	4	3/4-10	25.4	95.3
オプション72				114.3
オプション93				120.7

工場特注品(カブラ位置より45°です)

Cシリーズ単動スプリングリターンシリンダー寸法、価格

単位: mm

品番	価格	能力 (ton)	ストローク	必要油量 (cc)	A		C	D	E	H	J	K	ポア径	受圧面積 (cm ²)	能力 (kN)	能力 (MPa)	重量 (kg)
					最低地上高	最大高さ											
C 51C	36,850	4.5	25.4	18.0	110.3	138	38.1	1 1/2-16		25.4	3/4-16 x 15.9		28.6	6.4	44	440	1.0
C 53C	37,950		82.6	52.4	165.1	248											1.5
C 55C	39,330		133.4	85.2	215.9	349											1.8
C 57C	49,500		184.2	118.0	273.1	457											2.3
C 59C	59,400	10.2	235.0	150.8	323.9	559	57.2	2 1/4-14		38.1		42.8	14.4	100	999	2.6	
C 101C	42,080		25.4	36.1	92.1	117										1.8	
C 102C	42,350		54.0	78.7	120.7	175										2.3	
C 104C	47,580		104.8	150.8	171.5	276										3.0	
C 106C	52,530	14.0	155.6	224.5	247.7	403	69.9	2 3/4-16		44.5		50.8	20.3	139	1390	4.3	
C 108C	61,050		206.4	326.2	298.5	505										5.0	
C 1010C	62,700		257.2	370.4	349.3	606										5.9	
C 1012C	76,450		308.0	444.2	400.1	708										6.6	
C 1014C	82,230	23.4	358.8	517.9	450.9	810	85.7	3 5/16-12	49.2	57.2	1 1/2-16 x 25.4	9.5	65.1	33.2	229	2290	7.3
C 151C	51,980		25.4	50.8	123.8	149											3.4
C 152C	55,550		54.0	109.8	149.2	203											4.0
C 154C	62,700		104.8	211.4	200.0	305											5.2
C 156C	67,380	50.1	155.6	314.7	271.4	427	127.0	5-12	55.5	79.4		95.3	71.2	490	4904	6.9	
C 158C	78,100		206.4	417.9	322.2	529										8.1	
C 1510C	94,600		257.2	521.2	373.0	630										9.4	
C 1512C	115,780		308.0	624.5	423.8	732										10.5	
C 1514C	124,030	72.1	358.8	727.7	474.6	833	146.1	5 3/4-12	44.5	95.3	None	3.2	114.3	102.6	706	7058	11.8
C 1516C	127,880		406.4	824.4	522.3	929											12.8
C 251C	65,180		25.4	83.6	139.7	165											5.4
C 252C	69,030		50.8	168.8	165.1	216											6.3
C 254C	75,350	50.1	101.6	337.6	215.9	318	158.8	6 1/4-12	57.2	104.8		130.2	133.0	916	9163	8.0	
C 256C	85,800		158.8	527.8	273.1	432										9.8	
C 258C	113,580		209.6	696.6	323.9	533										11.6	
C 2510C	131,180		260.4	865.4	374.7	635										13.3	
C 2512C	166,380	93.6	311.2	1,035.8	425.5	737	158.8	6 1/2-12	57.2	104.8		130.2	133.0	916	9163	15.0	
C 2514C	167,750		362.0	1,204.7	476.3	838										16.7	
C 552C	129,530		50.8	362.2	174.6	225										14.7	
C 554C	139,980		108.0	768.7	231.8	340										18.7	
C 556C	148,230	72.1	158.8	1,130.9	282.6	441	146.1	5 3/4-12	44.5	95.3	None	3.2	114.3	102.6	706	7058	23.1
C 5510C	205,980		260.4	1,855.3	384.2	645											30.4
C 5513C	235,680		336.6	2,397.9	460.4	797											35.3
C 756C	283,250		155.6	1,596.4	314.3	470											33.3
C 7513C	342,930	93.6	333.4	3,420.6	492.1	826	158.8	6 1/2-12	57.2	104.8		130.2	133.0	916	9163	49.6	
C 1002C	273,630		50.8	675.3	219.1	270										28.5	
C 1006C	293,700		168.3	2,245.4	336.6	505										41.2	
C10010C	376,750		260.4	3,466.5	428.6	689										51.2	

Cシリーズシリンダーアクセサリー

品番	価格	番号	シリンダー能力	品番	価格	番号	シリンダー能力
208380	19,230		5	25746	15,710		5
208381	20,920		10	31772	19,560		10or15
208382	35,450		25	31776	22,790		25
202178	8,130		5	350095	17,250		5
202179	8,550		10or15	350094	21,660		10or15
202180	26,840		25	420059	34,490		25
350096	19,460		5	350099	19,930		5
350097	24,310		10	350100	24,310		10
350098	30,500		15	350184	35,810		15
420061	37,590		25	420064	52,900		25

シリンダーベースアタッチメント ネジ山アダプター すべり止めサドル



ピストン用クレビス

本体用クレビス

シリンダー取付用プレート