



140B型

## エネルギーチェーンシステム E4ライト & E4 / 4

- 開き部分と同じ部分が自由に組み合わせられます
- 下面が取り外せます
- エネルギーチェーンのクロスバーは両面取り外しも可能
- ケーブルクランプは、フランジ組付け可能
- チューブタイプもあります  
( R188B型、R198型、R1608型 )  
( R7728B型、R7838B型、R8840C型、R9850型 )
- 型式表示例  
2828B . 30 . 300 . 0

型式 幅インデックス  
曲げ半径 色

## エネルギーチェーンシステム E4ライト & E4 / 4 仕様

単位: mm

シリーズ	型式	タイプ	断面内の のり高さ	最大ホース ケーブル径	内のり幅	曲げ半径	ピッチ リンク = ℓ
E4ライト	140B	全リンクにクロスバー装着型	56	50	50,65,75,100,112,125,137,150,162,175,187,200,212,225,237,250,262,275,287,300,312,325,337,350,362,375,387,400,412,425,437,450,462,475,487,500,512,525,537,550,600	135,150,175,200,250,300,400,500	91mm/ℓ = 11ℓ/m (1001mm)
	142B	全リンクにクロスバー装着型	62	56	50,68,75,87,100,108,112,125,137,150,162,168,175,187,200,212,225,237,250,262,275,287,300,312,325,337,350,362,375,387,400	150,175,200,250,300,400,500	91mm/ℓ = 11ℓ/m (1001mm)
	150	全リンクにクロスバー装着型	80	74	50,75,100,112,125,137,150,162,175,187,200,212,225,237,250,262,275,287,300,312,325,337,350,362,375,387,400,412,425,437,450,462,475,487,500,512,525,537,550,600	150,200,250,300,350,400,500,550,600,650,1000	91mm/ℓ = 11ℓ/m (1001mm)
	1640	全リンクにクロスバー装着型	112	100	50,65,75,100,112,125,137,150,162,175,187,200,212,225,237,250,262,275,287,300,312,325,337,350,362,375,387,400,412,425,437,450,462,475,487,500,512,525,537,550,600	200,250,300,350,400,450,500,550,600	143mm/ℓ = 7ℓ/m (1001mm)
	R188B	密閉型	56	50	50,65,75,100,112,125,137,150,162,175,187,200,212,225,237,250,262,275,287,300,312,325,337,350,362,375,387,400,412,425,437,450,462,475,487,500,512,525,537,550,600	135,150,175,200,250,300,400,500	91mm/ℓ = 11ℓ/m (1001mm)
	R198	密閉型	80	74	50,75,100,112,125,137,150,162,175,187,200,212,225,237,250,262,275,287,300,312,325,337,350,362,375,387,400,412,425,437,450,462,475,487,500,512,525,537,550,600	150,200,250,300,350,400,500,550,600,650,1000	91mm/ℓ = 11ℓ/m (1001mm)
	R1608	密閉型	112	100	50,65,75,100,112,125,137,150,162,175,187,200,212,225,237,250,262,275,287,300,312,325,337,350,362,375,387,400,412,425,437,450,462,475,487,500,512,525,537,550,600	200,250,300,350,400,450,500,550,600	143mm/ℓ = 7ℓ/m (1001mm)
E4/4	2828B	全リンクにクロスバー装着型	32	28	50,68,75,87,100,108,112,125,137,150,162,168,175,187,200,212,225,237,250,262,275,287,300,312,325,337,350,362,375,387,400	63,75,100,125,150,175,200,220,250,300	56mm/ℓ = 18ℓ/m (1008mm)
	3838B	全リンクにクロスバー装着型	42	38	50,68,75,87,100,108,112,125,137,150,162,168,175,187,200,212,225,237,250,262,275,287,300,312,325,337,350,362,375,387,400	75,100,115,125,150,170,200,215,250,300,350	67mm/ℓ = 15ℓ/m (1005mm)
	4040C	全リンクにクロスバー装着型	56	50	50,65,75,100,112,125,137,150,162,175,187,200,212,225,237,250,262,275,287,300,312,325,337,350,362,375,387,400,412,425,437,450,462,475,487,500,512,525,537,550,600	135,150,175,200,240,250,300,400,500	91mm/ℓ = 11ℓ/m (1001mm)
	5050	全リンクにクロスバー装着型	80	74	50,65,75,100,112,125,137,150,162,175,187,200,212,225,237,250,262,275,287,300,312,325,337,350,362,375,387,400,412,425,437,450,462,475,487,500,512,525,537,550,600	150,200,250,300,350,400,500,550,600,650,1000	91mm/ℓ = 11ℓ/m (1001mm)
	R7728B	密閉型	32	28	50,68,75,87,100,108,112,125,137,150,162,168,175,187,200,212,225,237,250,262,275,287,300,312,325,337,350,362,375,387,400	63,75,100,125,150,175,200,220,250,300	56mm/ℓ = 18ℓ/m (1008mm)
	R7838B	密閉型	42	38	50,68,75,87,100,108,112,125,137,150,162,168,175,187,200,212,225,237,250,262,275,287,300,312,325,337,350,362,375,387,400	75,100,115,125,150,170,200,215,250,300,350	67mm/ℓ = 15ℓ/m (1005mm)
	R8840C	密閉型	56	50	50,65,75,100,112,125,137,150,162,175,187,200,212,225,237,250,262,275,287,300,312,325,337,350,362,375,387,400,412,425,437,450,462,475,487,500,512,525,537,550,600	135,150,175,200,240,250,300,400,500	91mm/ℓ = 11ℓ/m (1001mm)
	R9850	密閉型	80	74	50,65,75,100,112,125,137,150,162,175,187,200,212,225,237,250,262,275,287,300,312,325,337,350,362,375,387,400,412,425,437,450,462,475,487,500,512,525,537,550,600	150,200,250,300,350,400,500,550,600,650,1000	91mm/ℓ = 11ℓ/m (1001mm)

注 E4ライトならびにE4/4の「1つおきのリンクにクロスバー装着型」につきましては、お問い合わせ願います。