

三菱 ギヤードモータ

単相インダクションGM-J2S形25W仕様・価格 コンデンサ運転形 周波数50/60Hz 電圧100V全閉自冷形

出力軸回転数 (rpm)	減速比	価 格		出力軸許容トルク (Nm)		出力軸許容 オーバリング 荷重(N)	出力軸回転数 (rpm)		減速比	価 格		出力軸許容トルク (Nm)		出力軸許容 オーバリング 荷重(N)	
		端子箱無	ブレーキ付	50Hz	60Hz		50Hz	60Hz		端子箱無	ブレーキ付	50Hz	60Hz		
500	600	1/3	15,100		0.45	0.37	245	50	60	1/30	15,600		4.51	3.72	392
300	360	1/5	15,100		0.75	0.63	245	37.5	45	1/40	15,600		6.08	5.10	392
200	240	1/7.5	15,100		1.18	0.98	245	30	36	1/50	16,300		7.15	5.98	392
150	180	1/10	15,100		1.57	1.27	245	25	30	1/60	16,300		8.53	7.06	392
120	144	1/12.5	15,100		1.86	1.57	245	20	24	1/75	16,300		9.80	8.33	392
100	120	1/15	15,100		2.25	1.86	343	16.7	20	1/90	16,300		9.80	9.80	392
75	90	1/20	15,100		2.94	2.45	392	15	18	1/100	16,300		9.80	9.80	392
60	72	1/25	15,600		3.63	2.94	392	12.5	15	1/120	16,300		9.80	9.80	392

単相インダクションGM-J2S形40W仕様・価格 コンデンサ運転形 周波数50/60Hz 電圧100V全閉自冷形

500	600	1/3	18,500		0.72	0.60	294	50	60	1/30	19,000		6.57	5.49	539
300	360	1/5	18,500		1.18	0.98	294	37.5	45	1/40	19,000		8.62	7.15	588
200	240	1/7.5	18,500		1.76	1.47	294	30	36	1/50	19,600		10.8	8.92	637
150	180	1/10	18,500		2.35	1.96	294	25	30	1/60	19,600		12.3	10.8	686
120	144	1/12.5	18,500		2.94	2.45	294	20	24	1/75	19,600		16.2	13.2	686
100	120	1/15	18,500		3.53	2.94	343	16.7	20	1/90	19,600		19.6	19.1	686
75	90	1/20	18,500		4.41	3.63	441	15	18	1/100	19,600		20.6	19.6	686
60	72	1/25	19,000		5.49	4.61	490	12.5	15	1/120	19,600		20.6	20.6	686

単相インダクションGM-J2S形60W仕様・価格 コンデンサ運転形 周波数50/60Hz 電圧100V全閉外扇形

500	600	1/3	23,200		1.08	0.88	392	50	60	1/30	25,200		9.8	8.33	539
300	360	1/5	23,200		1.76	1.47	392	37.5	45	1/40	25,200		13.2	10.8	784
200	240	1/7.5	23,200		2.65	2.25	392	30	36	1/50	25,200		16.7	13.7	882
150	180	1/10	23,200		3.53	3.04	392	25	30	1/60	25,200		19.6	16.7	882
120	144	1/12.5	24,500		4.41	3.63	392	20	24	1/75	25,700		20.6	19.1	980
100	120	1/15	24,500		5.39	4.51	392	16.7	20	1/90	25,700		20.6	19.6	1080
75	90	1/20	24,500		6.86	5.59	441	15	18	1/100	25,700		20.6	20.6	1080
60	72	1/25	25,200		8.82	7.25	490	12.5	15	1/120	25,700		20.6	20.6	1080

単相インダクションGM-J2S形90W仕様・価格 コンデンサ運転形 周波数50/60Hz 電圧100V全閉外扇形

500	600	1/3	25,400		1.67	1.37	588	50	60	1/30	27,500		14.7	12.7	686
300	360	1/5	25,400		2.74	2.25	588	37.5	45	1/40	27,500		19.6	19.1	784
200	240	1/7.5	25,400		4.12	3.43	588	30	36	1/50	27,500		20.6	19.6	882
150	180	1/10	25,400		5.39	4.51	588	25	30	1/60	27,500		20.6	20.6	980
120	144	1/12.5	26,700		6.37	5.29	588	20	24	1/75	28,100		20.6	20.6	1080
100	120	1/15	26,700		7.35	6.17	588	16.7	20	1/90	28,100		20.6	20.6	1080
75	90	1/20	26,700		10.3	8.62	588	15	18	1/100	28,100		20.6	20.6	1080
60	72	1/25	27,500		12.3	10.8	588	12.5	15	1/120	28,100		20.6	20.6	1080

単相リバーシブルGM-J2R形25W仕様・価格 30分定格 周波数50/60Hz 電圧100V全閉自冷形

出力軸回転数 (rpm)	減速比	価 格		出力軸許容トルク (Nm)		出力軸許容 オーバリング 荷重(N)	出力軸回転数 (rpm)		減速比	価 格		出力軸許容トルク (Nm)		出力軸許容 オーバリング 荷重(N)	
		端子箱無	ブレーキ付	50Hz	60Hz		50Hz	60Hz		端子箱無	ブレーキ付	50Hz	60Hz		
500	600	1/3	15,600	28,600	0.45	0.37	245	50	60	1/30	16,300	29,200	4.51	3.72	392
300	360	1/5	15,600	28,600	0.75	0.63	245	37.5	45	1/40	16,300	29,200	6.08	5.1	392
200	240	1/7.5	15,600	28,600	1.18	0.98	245	30	36	1/50	16,700	29,800	7.15	5.98	392
150	180	1/10	15,600	28,600	1.57	1.27	245	25	30	1/60	16,700	29,800	8.53	7.06	392
120	144	1/12.5	15,600	28,600	1.86	1.57	245	20	24	1/75	16,700	29,800	9.8	8.33	392
100	120	1/15	15,600	28,600	2.25	1.86	343	16.7	20	1/90	16,700	29,800	9.8	9.8	392
75	90	1/20	15,600	28,600	2.94	2.45	392	15	18	1/100	16,700	29,800	9.8	9.8	392
60	72	1/25	16,300	29,200	3.63	2.94	392	12.5	15	1/120	16,700	29,800	9.8	9.8	392

単相リバーシブルGM-J2R形40W仕様・価格 30分定格 周波数50/60Hz 電圧100V全閉自冷形

500	600	1/3	19,000	36,000	0.72	0.60	294	50	60	1/30	19,600	36,500	6.57	5.49	539
300	360	1/5	19,000	36,000	1.18	0.98	294	37.5	45	1/40	19,600	36,500	8.62	7.15	588
200	240	1/7.5	19,000	36,000	1.76	1.47	294	30	36	1/50	20,100	37,100	10.8	8.92	637
150	180	1/10	19,000	36,000	2.35	1.96	294	25	30	1/60	20,100	37,100	12.3	10.8	686
120	144	1/12.5	19,000	36,000	2.94	2.45	294	20	24	1/75	20,100	37,100	16.2	13.2	686
100	120	1/15	19,000	36,000	3.53	2.94	343	16.7	20	1/90	20,100	37,100	19.6	19.1	686
75	90	1/20	19,000	36,000	4.41	3.63	441	15	18	1/100	20,100	37,100	20.6	19.6	686
60	72	1/25	19,600	36,500	5.49	4.61	490	12.5	15	1/120	20,100	37,100	20.6	20.6	686

単相リバーシブルGM-J2R形60W仕様・価格 30分定格 周波数50/60Hz 電圧100V全閉外扇形

500	600	1/3	24,200	43,600	1.08	0.88	392	50	60	1/30	26,400	45,500	9.8	8.33	539
300	360	1/5	24,200	43,600	1.76	1.47	392	37.5	45	1/40	26,400	45,500	13.2	10.8	784
200	240	1/7.5	24,200	43,600	2.65	2.25	392	30	36	1/50	26,400	45,500	16.7	13.7	882
150	180	1/10	24,200	43,600	3.53	3.04	392	25	30	1/60	26,400	45,500	19.6	16.7	882
120	144	1/12.5	25,600	44,900	4.41	3.63	392	20	24	1/75	27,000	46,100	20.6	19.1	980
100	120	1/15	25,600	44,900	5.39	4.51	392	16.7	20	1/90	27,000	46,100	20.6	19.6	1080
75	90	1/20	25,600	44,900	6.86	5.59	441	15	18	1/100	27,000	46,100	20.6	20.6	1080
60	72	1/25	26,400	45,500	8.82	7.25	490	12.5	15	1/120	27,000	46,100	20.6	20.6	1080



空圧・油圧・真空

直動システム・関連

ロボット・FA

制御・検出・計測

駆動・回転 5

軸受・素材・機械

動力伝達・伝動

搬送・運搬

ポンプ・送風機・粉体

工場設備・環境