

## ワールドKシリーズレバーシプルモーター仕様・価格

(ギヤヘッドは別価格です。●-174頁を参照願います)

モーターのタイプ・品名 リード線	上段:歯切シャフト、下段 価格 端子箱付	内:丸シャフト 価格	仕様	出力 W	電圧 V	周波数 Hz	電流 A	起動トルク mN・m	定格トルク mN・m	定格回転数 r/min	コンデンサ 容量μF
0RK1GN-AW2J (0RK1A-AW2J)	6,750		Ⓢ	1	単相100	50	0.12	8	10	1000	1.8
						60	0.125		8	1200	
0RK1GN-AW3U (0RK1A-AW3U)	6,750		Ⓢ	1	単相110 単相115	60	0.09	8	8	1200	1.2
							0.095				
0RK1GN-CW2J (0RK1A-CW2J)	6,950		Ⓢ	1	単相200	50	0.066	8	10	1000	0.45
						60	0.069		8	1200	
2RK6GN-AW2J (2RK6A-AW2J)	6,150	2RK6GN-AW2BJ (2RK6A-AW2BJ)	Ⓢ	6	単相100	50	0.25	50	49	1150	4.5
						60	0.30	45	41	1400	
2RK6GN-AW2U (2RK6A-AW2U)	6,150	2RK6GN-AW2BU (2RK6A-AW2BU)	Ⓢ	6	単相110 単相115	60	0.25	45	41	1450	3.5
							0.26				
2RK6GN-CW2J (2RK6A-CW2J)	6,350	2RK6GN-CW2BJ (2RK6A-CW2BJ)	Ⓢ	6	単相200	50	0.12	50	49	1150	1.0
						60	0.14	45	41	1400	
2RK6GN-CW2E (2RK6A-CW2E)	6,350	2RK6GN-CW2BE (2RK6A-CW2BE)	Ⓢ	6	単相220 単相230	50	0.12	45	49	1150	0.8
						60	0.11	45	41	1450	
						50	0.12	50	49	1200	
						60	0.12	45	41	1450	
3RK15GN-AW2J (3RK15A-AW2J)	6,750		Ⓢ	15	単相100	50	0.41	100	125	1200	7.5
60	0.50	105	1450								
3RK15GN-AW2U (3RK15A-AW2U)	6,750		Ⓢ	15	単相110 単相115	60	0.41	100	105	1450	6.0
							0.41				
3RK15GN-CW2J (3RK15A-CW2J)	6,950		Ⓢ	15	単相200	50	0.21	100	125	1200	1.8
						60	0.24		105	1450	
3RK15GN-CW2E (3RK15A-CW2E)	6,950		Ⓢ	15	単相220 単相230	50	0.20	100	125	1200	1.5
						60	0.21		105	1450	
						50	0.20		125	1200	
						60	0.21		105	1450	
4RK25GN-AW2J (4RK25A-AW2J)	7,450	4RK25GN-AW2TJ (4RK25A-AW2TJ)	Ⓢ	25	単相100	50	0.59	160	205	1200	10
						60	0.69	140	170	1450	
4RK25GN-AW2U (4RK25A-AW2U)	7,450	4RK25GN-AW2TU (4RK25A-AW2TU)	Ⓢ	25	単相110 単相115	60	0.56	140	170	1450	8.0
							0.56				
4RK25GN-CW2J (4RK25A-CW2J)	7,750	4RK25GN-CW2TJ (4RK25A-CW2TJ)	Ⓢ	25	単相200	50	0.32	160	205	1200	3.0
						60	0.40	140	170	1450	
4RK25GN-CW2E (4RK25A-CW2E)	7,750	4RK25GN-CW2TE (4RK25A-CW2TE)	Ⓢ	25	単相220 単相230	50	0.29	160	205	1200	2.5
						60	0.35	140	170	1450	
						50	0.30	160	205	1200	
						60	0.35	140	170	1450	
5RK40GN-AW2J (5RK40A-AW2J)	8,950	5RK40GN-AW2TJ (5RK40A-AW2TJ)	Ⓢ	40	単相100	50	0.91	300	315	1250	16
						60	1.09	260	270	1450	
5RK40GN-AW2U (5RK40A-AW2U)	8,950	5RK40GN-AW2TU (5RK40A-AW2TU)	Ⓢ	40	単相110 単相115	60	0.88	260	270	1450	12
							0.88				
5RK40GN-CW2J (5RK40A-CW2J)	9,350	5RK40GN-CW2TJ (5RK40A-CW2TJ)	Ⓢ	40	単相200	50	0.46	270	315	1250	4.0
						60	0.55	260	260	1500	
5RK40GN-CW2E (5RK40A-CW2E)	9,350	5RK40GN-CW2TE (5RK40A-CW2TE)	Ⓢ	40	単相220 単相230	50	0.43	270	315	1250	3.5
						60	0.48	260	260	1500	
						50	0.43	270	315	1250	
						60	0.48	260	260	1500	
5RK60GE-AW2J (5RK60A-AW2J)	10,550	5RK60GE-AW2TJ (5RK60A-AW2TJ)	Ⓢ	60	単相100	50	1.35	470	490	1200	25
						60	1.52	380	405	1450	
5RK60GE-AW2U (5RK60A-AW2U)	10,550	5RK60GE-AW2TU (5RK60A-AW2TU)	Ⓢ	60	単相110 単相115	60	1.27	380	405	1450	20
							1.27				
5RK60GE-CW2J (5RK60A-CW2J)	10,950	5RK60GE-CW2TJ (5RK60A-CW2TJ)	Ⓢ	60	単相200	50	0.66	450	490	1200	6.0
						60	0.79	380	405	1450	
5RK60GE-CW2E (5RK60A-CW2E)	10,950	5RK60GE-CW2TE (5RK60A-CW2TE)	Ⓢ	60	単相220 単相230	50	0.61	450	490	1200	5.0
						60	0.67	380	405	1450	
						50	0.63	470	490	1200	
						60	0.66	380	405	1450	
5RK90GE-AW2J (5RK90A-AW2J)	12,200	5RK90GE-AW2TJ (5RK90A-AW2TJ)	Ⓢ	90	単相100	50	1.85	630	700	1250	35
						60	2.16	590	585	1500	
5RK90GE-AW2U (5RK90A-AW2U)	12,200	5RK90GE-AW2TU (5RK90A-AW2TU)	Ⓢ	90	単相110 単相115	60	1.87	590	585	1500	30
							1.87				
5RK90GE-CW2J (5RK90A-CW2J)	12,600	5RK90GE-CW2TJ (5RK90A-CW2TJ)	Ⓢ	90	単相200	50	0.91	600	730	1200	8.0
						60	1.09	590	605	1450	
5RK90GE-CW3E (5RK90A-CW3E)	12,600	5RK90GE-CW3TE (5RK90A-CW3TE)	Ⓢ	90	単相220 単相230	50	0.83	600	730	1200	7.0
						60	0.96	590	605	1450	
						50	0.83	600	730	1200	
						60	0.95	590	605	1450	

Ⓢ:インピーダンスプロテクトされています。

Ⓢ:サーマルプロテクタを内蔵しています。モーターが何らかの原因で過熱すると、サーマルプロテクタが働いてモーターは停止します。

モーターの温度が下がると自動的に運転を再開しますので、点検作業は必ず電源を切って行ってください。

モーター銘板に記載されている品名は、コンデンサの種類を表す記号(J, U, E)がつかいません。

各種安全規格の認定は、モーター銘板商標(J, U, E)がつかないで取得しています。