




■HRS形、HR形標準形コンベヤチェーン(Sローラ形)(Rローラ形)(Fローラ形)寸法

チェーン番号	チェーンピッチ P (mm)	各ローラ寸法 (mm)								共通寸法 (mm)							
		Sローラ		Rローラ		Fローラ		内リンク内幅 W	内リンク	ピン				リンクプレート		平均引張強さ	
		外径 R	路面幅 E	外径 R	路面幅 E	フランジ幅 K	芯違い Z			径 D	長さ L	長さ L ₁	長さ L ₂	高さ H	厚さ T		
HRS03075-S、R、F	75	15.9	30.0	14.0	30.0	10.6	38	3.6	16.0	7.9	38.0	16.8	21.2	22.2	3.2	29.4	3000
HRS03100-S、R、F	100																
HRS03150-S、R、F	150																
HRS05075-S	75	22.2	40.0	19.0	40.0	14.5	50	4.8	22.0	11.0	53.4	23.9	29.5	31.8	4.7	68.6	7000
HRS05100-S、R、F	100																
HRS05150-S、R、F	150																
HR10105-S、R	101.6	20.1	38.1	19.0	—	—	—	—	22.6	9.5	53.0	24.2	28.8	25.4	4.7	53.9	5500
HR6608-S	66.27																
HR10108-S、R、F	101.6																
HR15208-S、R、F	152.4	25.4	50.8	26.0	50.8	20.0	65	7.0	30.2	11.0	65.7	30.6	35.1	28.6	6.3	78.5	8000
HR10011-S、R、F	100																
HR15011-S、R、F	150																
HR7813-S	78.11	31.8	44.5	27.0	44.5	20.0	60	7.0	31.6	15.8	87.5	40.0	47.5	38.1	7.9	132.4	13500
HR10113-S、R、F	101.6																
HR15215-S、R、F	152.4																
HR20015-S、R、F	200	34.9	65.0	32.0	65.0	24.0	85	8.0	37.1	15.8	87.5	40.0	47.5	44.5	7.9	186.3	19000
HR25015-S、R、F	250																
HR15219-S、R	152.4																
HR20019-S、R、F	200	39.7	80.0	44.0	80.0	34.0	105	12.0	51.4	18.9	111.3	51.4	59.9	50.8	9.5	245.2	25000
HR25019-S、R、F	250																
HR30019-S、R、F	300																
HR20026-S	200	44.5	106.0	50.0	100.0	38.0	130	13.0	57.2	22.1	119.6	55.3	64.3	63.5	9.5	313.8	32000
HR25026-S、R、F	250																
HR30026-S、R、F	300																
HR45026-S、R、F	450	50.8	125.0	56.0	125.0	42.0	160	14.0	66.7	25.2	143.7	67.6	76.1	76.2	12.7	475.6	48500
HR30048-S、R、F	300																
HR45048-S、R、F	450																
HR60048-S、R、F	600	57.2	140.0	65.0	140.0	49.0	180	16.5	77.0	31.6	169.3	81.6	87.7	76.2	16.0	529.6	54000
HR30054-S、R、F	300																
HR45054-S、R、F	450																
HR60054-S、R、F	600																

ローラの無いチェーンでトロリーコンベヤ、ログホールコンベヤなどに用いられます



■HB形ブシュドチェーン寸法

チェーン番号	チェーン ピッチ P (mm)	ブシュ 外径 R (mm)	内リンク 内幅 W (mm)	径 D (mm)	ピン			リンクプレート		平均引張強さ	
					長さ	高さ H (mm)	厚さ T (mm)				
								L (mm)	L ₁ (mm)	L ₂ (mm)	
HB10105	101.6	18.2	22.6	9.5	53.0	24.2	28.8	25.4	4.7	53.9	5500
HB10007	100.0	20.0	22.0	11.1	53.4	23.9	29.5	31.8	4.7	73.5	7500
HB6608	66.27	22.2	27.0	11.1	65.7	30.6	35.1	28.6	6.3	78.5	8000
HB10011	100.0	25.4	30.2	14.2	72.2	32.8	39.4	38.1	6.3	112.8	11500
HB15011	150.0										
HB7811	78.11	31.8	37.1	15.8	87.5	40.0	47.5	38.1	7.9	137.3	14000
HB10316	103.2	44.5	44.5	18.9	97.5	44.5	53.0	50.8	7.9	186.3	19000