





# 標準スプロケットホイール



B型 削り出し仕様)



B型 溶接仕様)



旧B型

●形番の表示

40 B 20

チェーンNo.

ボス形状

B : 片ボス KB:片ボス(旧B)

A : ベタ

歯数

HG型は頭形番前で表示

HG40B20

40B型・HG40型

材質: 鋼S35C焼入

K40B型(旧B型)

40A型・HG40型

共通寸法

形番	価格		ボス		軸径		形番	価格		ボス		形番	価格		歯数 Z	ピッチ径 Dp	外径 Do
	B型	HG型 歯先焼入	径 BD	幅 BL	下孔 d	最大孔径		旧B型 歯先焼入	径 BD	幅 BL	A型		HG型 歯先焼入	A型			
40B10	310		32	22	9.5	18	K40B10	350	28	25		40A10	240		10	41.10	46
40B11	330		36	22	10.5	20	K40B11	400	30	25		40A11	260	350	11	45.08	51
40B12	380		40	22	11.5	22	K40B12	460	34	25		40A12	270	390	12	49.07	53
40B13	390		37	22	13.5	20	K40B13	530	38	25		40A13	280	410	13	53.07	58
40B14	420		42	22	13.5	25	K40B14	540	42	25		40A14	300	440	14	57.07	63
40B15	430		46	22	13.5	28	K40B15	530	46	25		40A15	330	480	15	61.08	67
40B16	450		50	22	13.5	30	K40B16	600	50	25		40A16	360	560	16	65.10	71
40B17	510		54	22	13.5	32	K40B17	680	54	30		40A17	380	570	17	69.12	75
40B18	560		57	22	13.5	35	K40B18	750	54	30		40A18	410	550	18	73.14	78
40B19	600		62	22	13.5	40	K40B19	830	54	30		40A19	450	690	19	77.16	83
40B20	690		67	25	14	45	K40B20	880	56	40		40A20	420	640	20	81.18	88
40B21	750		71	25	14	48	K40B21	1,150	56	40		40A21	450	650	21	85.21	92
40B22	840		75	25	14	51	K40B22	1,190	56	40		40A22	500	680	22	89.24	96
40B23	890		77	25	14	51	K40B23	1,240	56	40		40A23	500	860	23	93.27	98
40B24	830		63	25	14	42	K40B24	1,290	56	40		40A24	550	760	24	97.30	104
40B25	880		63	25	14	42	K40B25	1,330	56	40		40A25	590	940	25	101.33	108
40B26	930		63	25	13	42	K40B26	1,440	56	40		40A26	620	970	26	105.36	112
40B27	960		63	25	13	42	K40B27	1,590	65	40		40A27	650	1,010	27	109.40	116
40B28	990		63	25	13	42	K40B28	1,750	65	40		40A28	680	1,040	28	113.43	120
40B29	1,080		63	25	13	42	K40B29	1,880	65	40		40A29	750	1,260	29	117.46	124
40B30	1,080		63	25	13	42	K40B30	1,580	65	40		40A30	690	950	30	121.50	128
40B31	1,330		68	28	14	45	K40B31	2,080	65	40		40A31	820		31	125.53	132
40B32	1,230		68	28	14	45	K40B32	2,190	65	40		40A32	750	1,210	32	129.57	137
40B33	1,460		68	28	14	45	K40B33	2,300	65	40		40A33	910		33	133.61	140
40B34	1,440		68	28	14	45	K40B34	2,400	65	40		40A34	900	1,260	34	137.64	145
40B35	1,430		68	28	14	45	K40B35	2,530	65	40		40A35	910	1,280	35	141.68	149
40B36	1,530		68	28	16	45	K40B36	2,680	68	35		40A36	990	1,490	36	145.72	153
40B37	1,800		68	28	16	45	K40B37	2,920	68	35		40A37	1,350		37	149.75	157
40B38	1,680		68	28	16	45	K40B38	3,000	68	35		40A38	1,150	1,550	38	153.79	161
40B39	1,760		68	28	16	45	K40B39	3,120	68	35		40A39	1,380		39	157.83	165
40B40	1,700		68	28	16	45	K40B40	3,190	68	35		40A40	1,150	1,640	40	161.87	169
40B41	2,300	2,470	73	32	16	48					40A41	1,540		41	165.91	173	
40B42	1,870		73	32	16	48					40A42	1,390	1,770	42	169.95	177	
40B43	2,450		73	32	16	48					40A43	1,710		43	173.98	181	
40B44	2,510		73	32	16	48					40A44	1,810	2,160	44	178.02	185	
40B45	2,060	3,030	73	32	16	48					40A45	1,530	1,920	45	182.06	189	
40B46	2,610		73	32	16	48					40A46	1,910	2,270	46	186.10	193	
40B47	2,670	3,560	73	32	16	48					40A47	1,880		47	190.14	197	
40B48	2,400	3,260	73	32	16	48					40A48	1,720	2,120	48	194.18	201	
40B49	2,790		73	32	16	48					40A49	2,050		49	198.22	205	
40B50	2,510	3,450	73	32	16	48					40A50	1,940	2,440	50	202.26	209	
40B51	3,040		73	32	16	48					40A51	2,220		51	206.30	214	
40B52	3,130		73	32	16	48					40A52	2,300	3,220	52	210.34	218	
40B53	3,230		73	32	16	48					40A53	2,390		53	214.38	222	
40B54	3,030	3,690	73	32	16	48					40A54	2,180	3,000	54	218.42	226	
40B55	3,400		73	32	16	48					40A55	2,550	3,600	55	222.46	230	
40B56	3,480		73	32	16	48					40A56	2,640		56	226.50	234	
40B60	3,440	4,200	73	32	16	48					40A57	2,820		57	230.54	238	
40B65	4,380		83	32	16	55					40A58	2,820		58	234.58	242	
40B70	4,630		83	32	16	55					40A59	2,910		59	238.62	246	
40B75	5,190		83	32	20	55					40A60	2,680	3,570	60	242.66	250	
40B80	6,940				19						40A65	3,370	4,700	65	262.87	270	
40B85	8,320				19						40A70	4,120	5,300	70	283.07	290	
40B90	9,050				19						40A75	4,680		75	303.28	311	
					19						40A80	6,210	6,570	80	323.49	331	
					19						40A85	6,450		85	343.69	351	
					19						40A90	7,190		90	363.90	371	

HG型はS35C歯先焼入品です

旧B型はS35C歯先焼入品です

HG型はS35C歯先焼入品です



空圧・油圧・真空

直動システム・関連

ロボット・FA

制御・検出・計測

駆動・回転

軸受・素材・機械

動力伝達・運動

搬送・運搬

ポンプ・送風機・粉体

工場設備・環境