

NSU形



NSU形ノーバックラッシギヤモジュール0.5(歯面切削) 材質:SUS304

形式	価格	モジュール	歯数Z	基準円直径	歯先円直径	形ばね数	歯幅b	穴径dd	ハブ外径	ハブ長さ	全長ℓ	ねじM
NS50SU 60B + 0505	19,300	0.5	60	30	31	BW	2	5	12	8	13	M3
NS50SU 70B + 0508	20,990	0.5	70	35	36	BW	2	5	16	8	13	M3
NS50SU 80B + 0508	23,640	0.5	80	40	41	BW	3	5	16	8	13	M3
NS50SU 90B + 0510	25,340	0.5	90	45	46	BW	3	5	10	20	8	M4
NS50SU 100B + 0510	28,090	0.5	100	50	51	BW	3	5	10	20	8	M4
NS50SU 120B + 0510	31,800	0.5	120	60	61	BW	4	5	10	20	8	M4

NS形ノーバックラッシギヤモジュール0.5/0.8/1.0(歯面切削) 材質:アルミニウム5056 S:S45Cクフライド処理


形式	価格	モジュール	歯数Z	基準円直径	歯先円直径	形ばね数	歯幅b	穴径dd	ハブ外径	ハブ長さ	全長ℓ	ねじM
NS50AL 60B + 0808	6,290	0.5	60	30	31	BS	1	8	16	8	16	M4
NS50AL 70B + 0808	6,620	0.5	70	35	36	BS	1	8	16	8	16	M4
NS50AL 80B + 0808	7,100	0.5	80	40	41	BS	1	8	20	8	16	M4
NS50AL 90B + 0810	7,430	0.5	90	45	46	BS	1	8	10	20	8	M4
NS50AL 100B + 0810	7,760	0.5	100	50	51	BS	1	8	10	20	8	M4
NS50AL 120B + 0810	8,470	0.5	120	60	61	BS	1	8	10	20	8	M4
NS80AL 50B + 0810	7,100	0.8	50	40	42	BS	1	8	10	20	10	M5
NS80AL 60B + 0810	7,760	0.8	60	48	50	BS	1	8	10	20	10	M5
NS80AL 70B + 0810	8,140	0.8	70	56	58	BS	1	8	10	20	10	M5
NS80S 80B + 0810	17,280	0.8	80	64	66	BW	2	8	10	20	10	M5
NS80S 90B + 0810	17,810	0.8	90	72	74	BW	2	8	10	20	10	M5
NS80S 100B + 0810	18,770	0.8	100	80	82	BW	2	8	10	24	10	M5
NS80S 120B + 0810	20,890	0.8	120	96	98	BW	2	8	10	24	10	M5
NS1AL 50B + 1010	7,810	1	50	50	52	BS	1	10	10	20	10	M6
NS1AL 60B + 1010	8,340	1	60	60	62	BS	1	10	10	20	10	M6
NS1S 70B + 1012	17,510	1	70	70	72	BW	2	10	12	24	10	M6
NS1S 80B + 1012	18,750	1	80	80	82	BW	2	10	12	24	10	M6
NS1S 90B + 1012	22,970	1	90	90	92	BW	3	10	12	24	10	M6
NS1S 100B + 1012	24,720	1	100	100	102	BW	3	10	12	30	10	M6
NS1S 120B + 1012	27,610	1	120	120	122	BW	3	10	12	30	10	M6

NSG形ノーバックラッシギヤモジュール0.5/0.8/1.0(歯面研削) 材質:SCM435


形式	価格	モジュール	歯数Z	基準円直径	歯先円直径	形ばね数	歯幅b	穴径dd	ハブ外径	ハブ長さ	全長ℓ	ねじM
NSG50S 60B + 0808	23,540	0.5	60	30	31	BS	1	8	16	8	16	M4
NSG50S 70B + 0808	25,020	0.5	70	35	36	BS	1	8	16	8	16	M4
NSG50S 80B + 0808	26,820	0.5	80	40	41	BS	1	8	20	8	16	M4
NSG50S 90B + 0810	28,840	0.5	90	45	46	BS	1	8	10	20	8	M4
NSG50S 100B + 0810	30,640	0.5	100	50	51	BS	1	8	10	20	8	M4
NSG50S 120B + 0810	35,090	0.5	120	60	61	BS	1	8	10	20	8	M4
NSG80S 50B + 0810	28,730	0.8	50	40	42	BS	1	8	10	20	10	M5
NSG80S 60B + 0810	30,640	0.8	60	48	50	BS	1	8	10	20	10	M5
NSG80S 70B + 0810	32,970	0.8	70	56	58	BS	1	8	10	20	10	M5
NSG80S 80B + 0810	34,770	0.8	80	64	66	BW	2	8	10	20	10	M5
NSG80S 90B + 0810	37,100	0.8	90	72	74	BW	2	8	10	20	10	M5
NSG80S 100B + 0810	39,930	0.8	100	80	82	BW	2	8	10	24	10	M5
NSG80S 120B + 0810	43,990	0.8	120	96	98	BW	2	8	10	24	10	M5
NSG1S 50B + 1010	29,980	1	50	50	52	BS	1	10	10	20	10	M6
NSG1S 60B + 1010	31,930	1	60	60	62	BS	1	10	10	20	10	M6
NSG1S 70B + 1012	33,890	1	70	70	72	BW	2	10	12	24	10	M6
NSG1S 80B + 1012	36,880	1	80	80	82	BW	2	10	12	24	10	M6
NSG1S 90B + 1012	43,060	1	90	90	92	BW	3	10	12	24	10	M6
NSG1S 100B + 1012	47,900	1	100	100	102	BW	3	10	12	30	10	M6
NSG1S 120B + 1012	52,530	1	120	120	122	BW	3	10	12	30	10	M6

ASG形ノーバックラッシギヤモジュール1.0/1.5/2.0(歯面研削) 材質:SCM435


形式	価格	モジュール	歯数Z	基準円直径	歯先円直径	歯幅b	穴径dd	ハブ外径	ハブ長さ	全長ℓ	ねじM
ASG1S 70B - 1012	30,600	1	70	70	72	10	12	40	10	20	6-M4
ASG1S 80B - 1012	33,580	1	80	80	82	10	12	45	10	20	6-M4
ASG1S 100B - 1012	40,690	1	100	100	102	10	12	60	10	20	6-M5
ASG1S 120B - 1015	46,870	1	120	120	122	10	15	80	10	20	6-M5
ASG1.5S 40B - 1515	26,780	1.5	40	60	63	15	15	35	15	30	6-M4
ASG1.5S 50B - 1520	30,490	1.5	50	75	78	15	20	45	15	30	6-M5
ASG1.5S 60B - 1520	35,230	1.5	60	90	93	15	20	60	15	30	6-M5
ASG1.5S 80B - 1520	44,600	1.5	80	120	123	15	20	80	15	30	6-M6
ASG2S 30B - 2015	29,150	2	30	60	64	20	15	35	20	40	6-M4
ASG2S 40B - 2020	34,820	2	40	80	84	20	20	50	20	40	6-M5
ASG2S 50B - 2020	41,000	2	50	100	104	20	20	60	20	40	6-M6
ASG2S 60B - 2025	47,280	2	60	120	124	20	25	80	20	40	6-M6



NSG形



ASG形



空圧・油圧・真空

直動システム・開連

ロボット・FA

制御・検出・計測

駆動・回転

軸受・素材・機械

動力伝達・伝動

搬送・運搬

ポンプ・送風機・粉体

工場設備・環境

