



A型



B型



KSSB型

●形式記号の組合せ  
SSB 10 12  
歯数

製品形式

SSB	S45Cボス付
SSA	S45Cボスナシ
SNB	キャストナイロンボス付
SNA	キャストナイロンボスナシ
SUB	SUS303ボス付
SUA	SUS303ボスナシ

モジュールピッチ (MP)

07	0.75	20	2.0	30	3.0
10	1.0	25	2.5	40	4.0

## MP2.5スパーギヤ価格

形式	S45C		キャストナイロン		SUS303		S45C孔加工付			
	ボス付	ボス無	ボス付	ボス無	ボス付	ボス無	孔寸法		孔寸法	
	SSB	SSA	SNB	SNA	SUB	SUA	KSSB	孔径	KSSB	孔径
2512	760	920	1,220	2,760	3,190	3,690				
2514	860	1,000	1,310	3,000	3,190	4,240				
2515	890	1,000	1,520	3,030	3,190	4,240	1,330	15K		
2516	960	1,000	1,590	3,070	3,420	4,350	1,420	15K		
2517	1,020	1,020	1,770	3,100	4,110	4,420				
2518	1,120	1,020	1,770	3,130	4,390	4,420	1,600	15K	1,660	18K
2519	1,180	1,020	2,130	3,150	4,650	4,490				
2520	1,310	1,030	2,150	3,170	5,090	4,550	1,720	15K	1,760	18K
2521	1,360	1,210	2,450	3,180	5,150	4,810			1,830	20K
2522	1,490	1,270	2,450	3,200	5,800	5,030	1,930	18K	1,980	20K
2523	1,550	1,280	2,600	3,200	5,980	5,250			2,050	25K
2524	1,620	1,280	2,600	3,210	6,550	5,470	2,020	18K	2,080	20K
2525	1,650	1,310	2,600	3,210	6,580	5,580	2,070	18K	2,150	20K
2526	1,750	1,490	2,920	3,220	7,110	5,930	2,230	18K	2,300	20K
2527	1,840	1,550	3,200	3,230	7,120	5,960			2,370	25K
2528	1,950	1,550	3,200	3,240	8,180	5,960	2,420	18K	2,480	20K
2529	2,010	1,680	3,650	3,250	8,500	6,410			2,540	25K
2530	2,130	1,680	3,650	3,260	9,100	6,450	2,720	20K	2,720	25K
2532	2,370	1,820	5,640	3,260		6,530	2,880	20K	2,970	25K
2534	2,570	2,000	7,180	3,330		6,910			2,970	30K
2535	2,600	2,030	7,180	3,330		7,000				
2536	2,720	2,130	7,180	3,530		7,800	3,260	20K	3,340	25K
2538	3,090	2,400	7,180	4,000		9,290			3,340	30K
2540	3,200	2,460	7,180	4,040		9,500	3,940	20K	4,010	25K
2542	3,440	2,860		4,750		10,500	4,480	20K	4,530	25K
2544	3,480	2,890		4,800		10,760			4,530	30K
2545	3,680	3,130		4,810		11,370	4,860	20K	4,900	25K
2546	4,000	3,280		5,400		12,240			4,900	30K
2548	4,060	3,280		5,420		13,080	5,170	20K	5,220	25K
2550	4,390	3,610		5,760		14,740	5,870	25K	5,930	30K
2552	4,480	4,050							5,930	35K
2554	4,830	4,050								
2555	4,930	4,060								
2556	5,400	4,400					6,370	25K	6,420	30K
2558	5,440	4,480							6,420	35K
2560	5,520	4,500					7,430	25K	7,500	30K
2562	6,350	6,000							7,500	35K
2564	6,480	6,030					8,370	25K	8,430	30K
2565	6,830	6,030							8,430	35K
2566	7,050	6,040								
2568	7,100	6,040								
2570	7,790	6,050								
2572	7,890	7,150								
2575	8,710	7,480								
2576	9,100	7,500								
2580	9,110	7,510								
2584		12,100								
2585	12,800	13,420								
2588		13,420								
2590	12,800	13,420								
2595	16,810	13,860								
25100	15,000	14,580								
25120	20,700	21,240								

## 共通寸法

単位: mm

歯数	主要寸法					
	ピッチ円	外径	歯幅	穴径	ボス径	ボス長
	P.C.D.	D	W	d <sub>17</sub>	B	BL
12	30	35	25	12	23	16
14	35	40	25	12	26	16
15	37.5	42.5	25	12	30	16
16	40	45	25	12	32	16
17	42.5	47.5	25	12	34	16
18	45	50	25	12	36	16
19	47.5	52.5	25	14	40	16
20	50	55	25	14	42	16
21	52.5	57.5	25	14	44	16
22	55	60	25	14	45	16
23	57.5	62.5	25	14	47	16
24	60	65	25	18	50	16
25	62.5	67.5	25	18	50	16
26	65	70	25	18	52	16
27	67.5	72.5	25	18	54	16
28	70	75	25	18	56	16
29	72.5	77.5	25	18	58	16
30	75	80	25	20	60	16
32	80	85	25	20	70	16
34	85	90	25	20	70	16
35	87.5	92.5	25	20	70	16
36	90	95	25	20	70	16
38	95	100	25	20	70	16
40	100	105	25	20	75	16
42	105	110	25	20	75	16
44	110	115	25	20	80	16
45	112.5	117.5	25	20	80	16
46	115	120	25	20	80	16
48	120	125	25	20	80	16
50	125	130	25	22	90	16
52	130	135	25	22	90	16
54	135	140	25	22	90	16
55	137.5	142.5	25	22	90	16
56	140	145	25	22	90	16
58	145	150	25	22	90	16
60	150	155	25	22	95	16
62	155	160	25	22	95	16
64	160	165	25	22	95	16
65	162.5	167.5	25	22	95	16
66	165	170	25	22	95	16
68	170	175	25	22	100	16
70	175	180	25	22	100	16
72	180	185	25	22	100	16
75	187.5	192.5	25	22	100	16
76	190	195	25	22	100	16
80	200	205	25	22	110	16
84	210	215	25	22	110	16
85	212.5	217.5	25	22	110	16
88	220	225	25	22	110	16
90	225	230	25	22	120	16
95	237.5	242.5	25	22	120	16
100	250	255	25	25	130	16
120	300	305	25	25	140	16

KSSB孔加工付歯車にはすべて押しねじが付属しています。

