



HR形、HR形標準形コンベヤチェン(Sローラ形)X(Rローラ形)X(Fローラ形)寸法

チェン番号	チェンピッチ P (mm)	各ローラ寸法 (mm)							共通寸法 (mm)							平均引張強さ (kN) (kgf)							
		Sローラ		Rローラ		Fローラ			ピン				リンクプレート										
		外径 R	外径 R	踏面幅 E	外径 R	踏面幅 E	フランジ径 K	芯違い Z	内リンク内幅 W	径 D	長さ L, L ₁ , L ₂			高さ H	厚さ T								
HRS03075-S, R, F	75																						
HRS03100-S, R, F	100	15.9	30.0	14.0	30.0	10.6	38	3.6	16.0	7.9	38.0	16.8	21.2	22.2	3.2	29.4	3000						
HRS03150-S, R, F	150																						
HRS05075-S	75																						
HR05100-S, R, F	100	22.2	40.0	19.0	40.0	14.5	50	4.8	22.0	11.0	53.4	23.9	29.5	31.8	4.7	68.6	7000						
HR05150-S, R, F	150																						
HR10105-S, R	101.6	20.1	38.1	19.0	-	-	-	-	22.6	9.5	53.0	24.2	28.8	25.4	4.7	53.9	5500						
HR6608-S	66.27																						
HR10108-S, R, F	101.6	22.2	44.5	23.0	44.5	18.0	55	6.5	27.0	11.0	65.7	30.6	35.1	28.6	6.3	78.5	8000						
HR15208-S, R, F	152.4	25.4	50.8	26.0	50.8	20.0	65	7.0	30.2		68.0	31.4	36.6	38.1									
HR10011-S, R, F	100																						
HR15011-S, R, F	150	29.0	50.8	26.7	50.8	20.0	65	7.0	30.2	14.2	72.2	32.8	39.4	38.1	6.3	112.8	11500						
HR7813-S	78.11																						
HR10113-S, R, F	101.6	31.8	44.5	27.0	44.5	20.0	60	7.0	31.6	15.8	87.5	40.0	47.5	38.1	7.9	132.4	13500						
HR15215-S, R, F	152.4		57.2		57.2	25.0	75	9.0			81.3	37.3	44.0										
HR20015-S, R, F	200	34.9		32.0					37.1	15.8	87.5	40.0	47.5	44.5	7.9	186.3	19000						
HR25015-S, R, F	250		65.0		65.0	24.0	85	8.0															
HR15219-S, R	152.4		69.9	32.5	-	-	-	-	37.1	18.9	97.1	44.3	52.8										
HR20019-S, R, F	200																						
HR25019-S, R, F	250	39.7	80.0	44.0	80.0	34.0	105	12.0	51.4	18.9	111.3	51.4	59.9	50.8	9.5	245.2	25000						
HR30019-S, R, F	300																						
HR20026-S	200		-	-	-	-	-	-															
HR25026-S, R, F	250																						
HR30026-S, R, F	300	44.5	106.0	50.0	100.0	38.0	130	13.0	57.2	22.1	119.6	55.3	64.3	63.5	9.5	313.8	32000						
HR45026-S, R, F	450																						
HR30048-S, R, F	300																						
HR45048-S, R, F	450	50.8	125.0	56.0	125.0	42.0	160	14.0	66.7	25.2	143.7	67.6	76.1	76.2	12.7	475.6	48500						
HR60048-S, R, F	600																						
HR30054-S, R, F	300																						
HR45054-S, R, F	450	57.2	140.0	65.0	140.0	49.0	180	16.5	77.0	31.6	169.3	81.6	87.7	76.2	16.0	529.6	54000						
HR60054-S, R, F	600																						

ローラの無いチェンでトロリーコンベヤ、ログホールコンベヤなどに用いられます



HB形プッシュドチェン寸法

チェン番号	チェンピッチ P (mm)	プッシュ 外径 R (mm)	内リンク 内幅 W (mm)	径 D (mm)	ピン			リンクプレート		平均引張強さ (kN) (kgf)	
					長さ L (mm)	長さ L ₁ (mm) L ₂ (mm)		高さ H (mm)	厚さ T (mm)		
HB10105	101.6	18.2	22.6	9.5	53.0	24.2	28.8	25.4	4.7	53.9	5500
HB10007	100.0	20.0	22.0	11.1	53.4	23.9	29.5	31.8	4.7	73.5	7500
HB6608	66.27	22.2	27.0	11.1	65.7	30.6	35.1	28.6	6.3	78.5	8000
HB10011	100.0										
HB15011	150.0	25.4	30.2	14.2	72.2	32.8	39.4	38.1	6.3	112.8	11500
HB7811	78.11	31.8	37.1	15.8	87.5	40.0	47.5	38.1	7.9	137.3	14000
HB10316	103.2	44.5	44.5	18.9	97.5	44.5	53.0	50.8	7.9	186.3	19000