



SP型中間スプライン軸付タイプ仕様、寸法

●加工形状


SP- -03A(新JIS片側キー)




SP- -33A(新JIS両側キー)




SP- -08A(旧JIS片側キー)




SP- -88A(旧JIS両側キー)



SP- -09A(片側クイックチェンジ)



SP- -99A(両側クイックチェンジ)




品番	d	L	伸縮	A	B	主要寸法 (mm)							
						スプライン諸元 S	E	LC	D	F	G	H	
SP-08-	A	8	163	+19 -11	127	65	インボリュート 大径=10 m=0.75 z=11	20	36	17	11	39	65
SP-08-09A		8	167	+17 -13	129	65	インボリュート 大径=10 m=0.75 z=11	20	36	17	13	37	65
SP-08-99A		8	169	+17 -13	129	65	インボリュート 大径=10 m=0.75 z=11	20		17	13	37	65
SP-10-	A	10	177	+17 -13	135	65	インボリュート 大径=12 m=1.0 z=10	25	42	19	13	37	65
SP-12-	A	12	225	+16 -16	173	88	16 × 13 × 3.5-6	40	52	23	16	56	89
SP-14-	A	14	240	+14 -18	181	87	16 × 13 × 3.5-6	40	59	23	18	54	89
SP-16-	A	16	308	+35 -23	234	115	20 × 16 × 4-6	40	74	30	23	75	120
SP-18-	A	18	327	+30 -26	246	115	20 × 16 × 4-6	40	81	30	28	70	120
SP-20-	A	20	344	+33 -27	257	118	22 × 18 × 5-6	40	87	36	27	73	125
SP-22-	A	22	360	+28 -30	266	115	25 × 21 × 5-6	40	94	40	30	68	125
SP-25-	A	25	405	+38 -32	300	133	28 × 23 × 6-6	45	105	44	32	83	145
SP-30-	A	30	464	+35 -40	342	145	32 × 26 × 6-6	50	122	51	40	85	160
SP-35-	A	35	515	+35 -45	375	150	38 × 32 × 8-6	50	140	60	45	85	170
SP-40-	A	40	574	+35 -50	417	165	42 × 36 × 8-6	60	157	67	50	95	190
SP-45-	A	45	637	+35 -55	461	180	45 × 41 × 8-8	70	176	75	55	105	210
SP-50-	A	50	697	+35 -60	506	200	52 × 46 × 9-8	80	191	83	60	115	230

SP型中間スプライン軸付タイプ価格

加工形状 品番	両側 ピン止め		新JIS 片側キー		新JIS 両側キー		旧JIS 片側キー		旧JIS 両側キー		片側クイック チェンジ		両側クイック チェンジ		カバー付 C	寸法 LQ
	00A	03A	33A	08A	88A	09A	99A									
08	14,400	14,600	14,800			16,700	19,500							960		
10	14,700	15,000	15,300	15,000	15,300	17,400	20,500							960	42	
12	15,900	16,200	16,500	16,200	16,500	18,800	22,100							960	52	
14	17,100	17,400	17,700	17,400	17,700	20,200	23,800							960	59	
16	18,700	19,000	19,300	19,000	19,300	22,000	26,000	1,200	74							
18	21,300	21,800	22,300	21,800	22,300	25,800	30,900	1,680	81							
20	23,700	24,200	24,700	24,200	24,700	29,400	35,800	1,680	87							
22	26,400	27,000	27,600	27,000	27,600	34,000	42,300	1,920	94							
25	31,400	32,100	32,800	32,100	32,800	40,500	50,500	1,920	105							
30	41,500	42,700	43,900	42,700	43,900	54,400	68,500	4,320	122							
35	81,600	84,000	86,400	84,000	86,400			15,360								
40	93,600	96,000	98,400	96,000	98,400			16,320								
45	116,400	120,000	123,600	120,000	123,600			17,280								
50	140,400	144,000	147,600	144,000	147,600			19,200								

SC型、SD型SP型付属品

型式	強力		平行		セット		リング		型式	強力		平行		セット		リング	
	セットピン SKP00	強力ピン SKP11	セットピン SSP00	リング SRS00	セットピン SKP00	強力ピン SKP11	セットピン SSP00	リング SRS00									
03	100			30	18	140	140	140	50								
04	100			30	20	160	160	160	60								
05	100			30	22	180	180	180	80								
06	100	100	100	30	25	200	200	200	90								
08	100	100	100	30	30	400	400	400	120								
10	100	100	100	30	35	500	500	500	140								
12	120	120	120	40	40	600	600	600	160								
14	120	120	120	40	45	700	700	700	180								
16	120	120	120	40	50	800	800	800	200								



空圧・油圧・真空

直動システム・関連

ロボット・FA

制御・検出・計測

駆動・回転

軸受・素材・機械

動力伝達・伝動

搬送・運搬

ポンプ・送風機・粉体

工場設備・環境