

スチール製ローラコンベヤ

(株)マキテック

311561

S-5714NBスチール製ローラコンベヤ



フレーム寸法I×K×f(mm)	□90×30×2.3
コンベヤ機高 H(mm)	100
標準機長 L(mm)	1,000・1,500・2,000・3,000
ローラ間隔 P(mm)	75・100・150
カーブ R	内900R

ローラ寸法D×t×d(mm)	57.2×1.4× 12 ヂキ付
ローラ巾製作範囲	90 ~ 990
W(mm)フリーサイズ	特殊仕様となります
ベアリング	規格ベアリング #6201
軸 (mm)	12パイプ 両ツブシ

ローラ巾 W(mm)	90	150	240	305	390	490	620	690	790	890	990
フレーム内巾W+10(mm)	100	160	250	315	400	500	630	700	800	900	1,000
機巾W+70(mm)	160	220	310	375	460	560	690	760	860	960	1,060
ローラ強度 (kg)	180	170	170	150	110	90	75	65	55	50	45
コンベヤ重量目安	75P 38.8	44.4	55.4	60.8	71.7	82.1	93.7	104.7	115.7	126.1	136.8
3,000L (kg)	100P 33.0	38.0	47.3	51.5	60.0	68.4	78.9	85.4	91.9	100.3	108.7

S-5714NB形価格

ローラ間隔	機長	90W	150W	240W	305W	390W	490W	620W	690W	790W	890W	990W
75P	3,000L	51,900	55,800	63,700	67,000	72,100	80,200	87,700	95,800	104,200	113,300	125,400
	2,000L	35,900	38,500	43,800	46,000	49,400	54,900	59,800	65,300	70,800	77,900	85,400
	1,000L	19,500	20,800	23,500	24,600	26,500	29,300	31,900	34,700	37,600	41,300	45,200
	内900R×90°	46,000	48,400	54,200	55,800	59,200	63,000	69,000	72,600	80,000	87,600	89,500
100P	3,000L	41,900	44,800	50,700	53,400	57,100	63,400	69,000	75,100	81,500	89,300	98,000
	2,000L	29,200	31,200	35,300	37,000	39,800	44,100	48,200	52,300	56,700	62,200	68,200
	1,000L	16,100	17,200	19,300	20,100	21,600	23,900	26,000	28,200	30,500	33,400	36,600
	内900R×90°	43,500	45,500	49,900	51,800	54,900	59,300	63,700	68,100	72,600	79,800	87,300
150P	3,000L	32,700	34,900	38,900	40,800	43,600	49,200	52,100	56,400	60,900	67,000	73,400
	2,000L	22,700	24,100	26,700	27,900	29,700	32,700	36,000	38,200	41,100	45,300	49,600
	1,000L	38,600	13,600	15,200	15,700	16,600	18,200	19,600	21,000	22,400	24,600	27,000
	内900R×90°	11,400	40,600	44,100	45,500	48,200	52,000	55,300	59,100	62,900	69,100	75,700
ローラ単品	軸付	1,140	1,250	1,440	1,530	1,830	2,010	2,200	2,310	2,610	2,870	3,150
	軸なし	1,000	1,090	1,240	1,310	1,560	1,710	1,870	1,950	2,200	2,420	2,640

R-5726スチール製ローラコンベヤ



フレーム寸法I×K×f(mm)	□90×30×4.5
コンベヤ機高 H(mm)	100
標準機長 L(mm)	1,000・1,500・2,000・3,000
ローラ間隔 P(mm)	75・100・150・200
カーブ R	内900R

ローラ寸法D×t×d(mm)	57.2×2.6× 17 ヂキ付
ローラ巾製作範囲	100 ~ 1,000
W(mm)フリーサイズ	特殊仕様となります
ベアリング	削り出しベアリング
軸 (mm)	17パイプ 半月

ローラ巾 W(mm)	100	200	300	400	500	600	700	800	900	1,000
機巾W+75(mm)	175	275	375	475	575	675	775	875	975	1,075
ローラ強度 (kg)	390	360	328	280	224	177	160	132	112	104
コンベヤ重量目安	75P 51.0	67.0	83.4	99.8	116.2	132.6	149.0	165.4	181.8	198.2
3,000L (kg)	100P 46.0	58.0	70.4	82.2	95.2	107.6	120.0	132.4	144.8	157.2
ローラ・軸付重量目安 (kg)	0.5	0.9	1.3	1.7	2.1	2.5	2.9	3.3	3.7	4.1

R-5726形価格

ローラ間隔	機長	100W	150W	200W	250W	300W	350W	400W	500W	600W	800W	1,000W
75P	3,000L	81,900	87,800	93,200	99,100	104,900	111,100	116,900	129,100	141,100	166,500	200,300
	2,000L	53,500	57,200	60,800	64,700	68,500	72,500	76,300	84,100	92,200	108,600	130,400
	1,000L	28,200	30,100	32,000	34,000	36,100	38,100	39,900	44,000	48,000	56,400	67,800
	内900R×90°	61,600	65,700	70,000	73,700	77,400	81,200	85,100	92,600	100,400	116,500	139,900
100P	3,000L	67,100	71,300	75,800	80,300	84,700	89,200	93,900	102,800	112,200	131,500	158,100
	2,000L	43,900	46,700	49,700	52,600	55,600	58,600	61,600	67,600	73,800	86,700	104,200
	1,000L	23,400	24,900	26,400	27,900	29,300	30,900	32,400	35,600	38,800	45,200	54,400
	内900R×90°	55,000	57,800	60,700	63,800	66,800	69,800	72,800	79,100	85,500	98,300	118,000
150P	3,000L	52,800	56,000	59,100	62,200	65,000	68,500	71,300	78,200	84,700	98,100	117,900
	2,000L	34,000	36,200	38,200	40,200	42,200	44,400	46,400	50,700	55,100	63,800	76,600
	1,000L	17,400	18,400	19,300	20,300	21,100	22,200	23,000	25,100	27,100	31,200	37,400
	内900R×90°	47,800	50,200	52,400	54,800	57,100	59,500	61,800	66,600	71,500	81,500	98,000
200P	3,000L	43,600	45,700	48,000	50,600	53,000	55,300	57,700	62,600	67,500	77,600	93,400
	2,000L	28,000	29,700	31,200	32,800	34,400	36,100	37,600	41,000	44,200	51,200	61,600
	1,000L	15,600	16,200	17,100	18,000	18,700	19,600	20,400	22,200	24,000	27,300	32,800
	内900R×90°	44,600	47,000	48,600	51,000	52,600	55,600	57,600	60,900	65,100	71,100	77,500
ローラ単品	軸付	2,070	2,310	2,440	2,640	2,780	3,050	3,210	3,530	3,900	4,860	5,840
	軸なし	1,810	1,980	2,080	2,250	2,350	2,520	2,630	2,950	3,210	3,900	4,680

空圧・油圧・真空

直動システム・関連

ロボット・FA

制御・検出・計測

駆動・回転

軸受・素材・機械

動力伝達・伝動

搬送・運搬

ポンプ・送風機・粉体

工場設備・環境