

# スチール製ローラコンベヤ

(株)マキテック

311561

## S-5714NBスチール製ローラコンベヤ



フレーム寸法I×K×f(mm)	□90×30×2.3
コンベヤ機高 H (mm)	100
標準機長 L (mm)	1,000・1,500・2,000・3,000
ローラ間隔 P (mm)	75・100・150
カーブ R	内900R

ローラ寸法D×t×d(mm)	57.2×1.4× 12 ヂキ付
ローラ巾製作範囲	90 ~ 990
W (mm)フリーサイズ	特殊仕様となります
ベアリング	規格ベアリング #6201
軸 (mm)	12パイプ 両ツブシ

ローラ巾 W (mm)	90	150	240	305	390	490	620	690	790	890	990
フレーム内巾W+10(mm)	100	160	250	315	400	500	630	700	800	900	1,000
機巾W+70(mm)	160	220	310	375	460	560	690	760	860	960	1,060
ローラ強度 (kg)	180	170	170	150	110	90	75	65	55	50	45
コンベヤ重量目安	75P 38.8	44.4	55.4	60.8	71.7	82.1	93.7	104.7	115.7	126.1	136.8
3,000L (kg)	100P 33.0	38.0	47.3	51.5	60.0	68.4	78.9	85.4	91.9	100.3	108.7

### S-5714NB形価格

ローラ間隔	機長	90W	150W	240W	305W	390W	490W	620W	690W	790W	890W	990W
75P	3,000L	54,500	58,600	66,900	70,400	75,800	84,300	92,100	100,600	109,500	119,000	131,700
	2,000L	37,700	40,500	46,000	48,300	51,900	57,700	62,800	68,600	74,400	81,800	89,700
	1,000L	20,500	21,900	24,700	25,900	27,900	30,800	33,500	36,500	39,500	43,400	47,500
	内900R×90°	48,300	50,900	57,000	58,600	62,200	66,200	72,500	76,300	84,000	92,000	94,000
100P	3,000L	44,000	47,100	53,300	56,100	60,000	66,600	72,500	78,900	85,600	93,800	102,900
	2,000L	30,700	32,800	37,100	38,900	41,800	46,400	50,700	55,000	59,600	65,400	71,700
	1,000L	17,000	18,100	20,300	21,200	22,700	25,100	27,300	29,700	32,100	35,100	38,500
	内900R×90°	45,700	47,800	52,400	54,400	57,700	62,300	66,900	71,600	76,300	83,800	91,700
150P	3,000L	34,400	36,700	40,900	42,900	45,800	51,700	54,800	59,300	64,000	70,400	77,100
	2,000L	23,900	25,400	28,100	29,300	31,200	34,400	37,800	40,200	43,200	47,600	52,100
	1,000L	12,000	14,300	16,000	16,500	17,500	19,200	20,600	22,100	23,600	25,900	28,400
	内900R×90°	40,600	42,700	46,400	47,800	50,700	54,600	58,100	62,100	66,100	72,600	79,500
ローラ単品	軸付	1,200	1,320	1,520	1,610	1,930	2,120	2,310	2,430	2,750	3,020	3,310
	軸なし	1,050	1,150	1,310	1,380	1,640	1,800	1,970	2,050	2,310	2,550	2,780

## R-5726スチール製ローラコンベヤ



フレーム寸法I×K×f(mm)	□90×30×4.5
コンベヤ機高 H (mm)	100
標準機長 L (mm)	1,000・1,500・2,000・3,000
ローラ間隔 P (mm)	75・100・150・200
カーブ R	内900R

ローラ寸法D×t×d(mm)	57.2×2.6× 17 ヂキ付
ローラ巾製作範囲	100 ~ 1,000
W (mm)フリーサイズ	特殊仕様となります
ベアリング	削り出しベアリング
軸 (mm)	17パイプ 半月

ローラ巾 W (mm)	100	200	300	400	500	600	700	800	900	1,000
機巾W+75(mm)	175	275	375	475	575	675	775	875	975	1,075
ローラ強度 (kg)	390	360	328	280	224	177	160	132	112	104
コンベヤ重量目安	75P 51.0	67.0	83.4	99.8	116.2	132.6	149.0	165.4	181.8	198.2
3,000L (kg)	100P 46.0	58.0	70.4	82.2	95.2	107.6	120.0	132.4	144.8	157.2
ローラ・軸付重量目安 (kg)	0.5	0.9	1.3	1.7	2.1	2.5	2.9	3.3	3.7	4.1

### R-5726形価格

ローラ間隔	機長	100W	150W	200W	250W	300W	350W	400W	500W	600W	800W	1,000W
75P	3,000L	86,000	92,200	97,900	104,100	110,200	116,700	122,800	135,600	148,200	174,900	210,400
	2,000L	56,200	60,100	63,900	68,000	72,000	76,200	80,200	88,400	96,900	114,100	137,000
	1,000L	29,700	31,700	33,600	35,700	38,000	40,100	41,900	46,200	50,400	59,300	71,200
	内900R×90°	64,700	69,000	73,500	77,400	81,300	85,300	89,400	97,300	105,500	122,400	146,900
100P	3,000L	70,500	74,900	79,600	84,400	89,000	93,700	98,600	108,000	117,900	138,100	166,100
	2,000L	46,100	49,100	52,200	55,300	58,400	61,600	64,700	71,000	77,500	91,100	109,500
	1,000L	24,600	26,200	27,800	29,300	30,800	32,500	34,100	37,400	40,800	47,500	57,200
	内900R×90°	57,800	60,700	63,800	67,000	70,200	73,300	76,500	83,100	89,800	103,300	123,900
150P	3,000L	55,500	58,800	62,100	65,400	68,300	72,000	74,900	82,200	89,000	103,100	123,800
	2,000L	35,700	38,100	40,200	42,300	44,400	46,700	48,800	53,300	57,900	67,000	80,500
	1,000L	18,300	19,400	20,300	21,400	22,200	23,400	24,200	26,400	28,500	32,800	39,300
	内900R×90°	50,200	52,800	55,100	57,600	60,000	62,500	64,900	70,000	75,100	85,600	102,900
200P	3,000L	45,800	48,000	50,400	53,200	55,700	58,100	60,600	65,800	70,900	81,500	98,100
	2,000L	29,400	31,200	32,800	34,500	36,200	38,000	39,500	43,100	46,500	53,800	64,700
	1,000L	16,400	17,100	18,000	18,900	19,700	20,600	21,500	23,400	25,200	28,700	34,500
	内900R×90°	46,900	49,400	51,100	53,600	55,300	58,400	60,500	64,000	68,400	74,700	81,400
ローラ単品	軸付	2,180	2,430	2,570	2,780	2,920	3,210	3,380	3,710	4,100	5,110	6,140
	軸なし	1,910	2,080	2,190	2,370	2,470	2,650	2,770	3,100	3,380	4,100	4,920

空圧・油圧・真空

直動システム・関連

ロボット・FA

制御・検出・計測

駆動・回転

軸受・素材・機械

動力伝達・伝動

搬送・運搬

ポンプ・送風機・粉体

工場設備・環境