

# スチール製ローラコンベヤ

(株)マキテック

311561

## R-6023スチール製ローラコンベヤ



フレーム寸法L×K×H(mm)	□90×30×3.2
コンベヤ機高 H (mm)	102
標準機長 L (mm)	1,000・1,500・2,000・3,000
ローラ間隔 P (mm)	75・100・150・200
カーブ R	内900R

ローラ寸法D×t×d(mm)	60.5×2.3×15 ヌキ付
ローラ巾製作範囲	100~1,000 50とび
W (mm)フリーサイズ	特殊仕様となります。
ベアリング	削り出しベアリング
軸 (mm)	15パイプ 半月

ローラ巾 W (mm)	100	200	300	400	500	600	700	800	900	1,000
機 巾W+75(mm)	175	275	375	475	575	675	775	875	975	1,075
ローラ強度 (kg)	376	345	293	250	200	158	143	117	100	93
コンベヤ重量目安	75P	45.4	63.4	81.4	99.4	117.4	135.4	153.4	171.4	189.4
3,000L (kg)	100P	39.8	53.4	67.0	80.6	94.2	107.8	121.4	135.0	148.6
ローラ・軸付重量目安 (g)		0.6	1.0	1.4	1.9	2.3	2.8	3.2	3.6	4.1
									4.5	

### R-6023形価格

ローラ間隔	機長	100W	150W	200W	250W	300W	350W	400W	500W	600W	800W	1,000W
75P	3,000L	65,200	71,100	77,200	83,300	89,400	95,500	101,700	113,800	125,800	150,500	179,000
	2,000L	41,700	45,700	49,400	53,400	57,500	61,500	65,300	73,500	81,900	99,000	118,800
	1,000L	22,700	24,600	26,500	28,700	30,500	32,500	34,500	38,600	42,800	51,300	61,600
	内900R×90°	60,300	64,400	67,300	71,600	74,500	78,700	81,800	89,200	96,800	112,300	134,700
100P	3,000L	54,100	58,800	63,100	67,800	72,000	76,900	81,400	90,800	100,200	118,800	140,800
	2,000L	34,600	37,900	40,800	43,900	46,800	50,000	53,100	59,400	65,700	79,100	94,900
	1,000L	19,200	20,700	22,300	23,700	25,200	26,900	28,600	31,600	34,800	41,600	50,000
	内900R×90°	54,300	57,700	59,800	63,200	65,500	68,900	71,200	76,900	83,000	95,100	114,200
150P	3,000L	43,600	46,800	50,200	53,400	56,400	60,000	63,300	70,100	77,200	91,300	108,200
	2,000L	27,000	28,900	30,800	32,700	34,800	36,800	38,800	42,800	46,900	55,600	66,600
	1,000L	15,200	16,100	17,100	18,100	19,200	20,200	21,100	23,300	25,300	29,800	35,800
	内900R×90°	48,500	51,100	52,800	55,200	57,000	59,700	61,500	65,900	70,400	79,900	95,800
200P	3,000L	41,000	43,100	45,200	47,400	49,400	51,700	53,900	58,400	63,100	72,500	86,800
	2,000L	22,600	24,300	25,900	27,400	29,000	30,800	32,400	35,800	39,100	46,000	55,200
	1,000L	13,000	13,800	14,700	15,500	16,200	17,200	18,000	19,800	21,600	25,200	30,400
	内900R×90°	46,800	47,600	48,900	50,300	51,100	52,400	53,200	55,300	57,700	62,200	74,600
ローラ単品	軸付	1,370	1,580	1,720	1,960	2,110	2,310	2,430	2,740	3,110	3,880	4,650
	軸なし	1,180	1,360	1,470	1,690	1,840	1,980	2,080	2,300	2,610	3,270	3,930

## R-6038スチール製ローラコンベヤ



フレーム寸法L×K×H(mm)	□90×30×4.5
コンベヤ機高 H (mm)	100
標準機長 L (mm)	1,000・1,500・2,000・3,000
ローラ間隔 P (mm)	75・100・150・200
カーブ R	内900R

ローラ寸法D×t×d(mm)	60.5×3.8×20
ローラ巾製作範囲	100~1000
W (mm)フリーサイズ	製作できます
ベアリング	削り出しベアリング
軸 (mm)	20丸棒 半月

ローラ巾 W (mm)	100	200	300	400	500	600	700	800	900	1000
機 巾W+75(mm)	175	275	375	475	575	675	775	875	975	1075
ローラ強度 (kg)	570	538	505	475	475	475	450	420	400	380
コンベヤ重量目安	75P	65	94.6	124.6	154.6	184.6	214.6	244.6	274.6	304.6
3,000L (kg)	100P	56	78.7	101.3	123.9	146.5	169.1	191.7	214.3	236.9
ローラ・軸付重量目安 (kg)		0.9	1.6	2.3	3.1	3.8	4.6	5.3	6.0	6.8
									7.5	

### R-6038形価格

ローラ間隔	機長	100W	200W	300W	400W	500W	600W	700W	800W	900W	1000W
75P	3,000L	103,300	116,500	129,800	143,500	157,400	171,500	185,800	200,500	219,600	238,700
	2,000L	67,800	77,500	87,500	97,700	108,000	118,700	129,400	140,300	154,300	168,300
	1,000L	35,500	40,400	45,500	50,800	56,100	61,500	67,100	72,700	80,100	87,200
	内900R×90°	73,900	82,200	90,700	99,500	108,300	117,400	126,600	136,000	149,500	163,200
100P	3,000L	86,900	96,900	107,100	117,600	128,100	139,100	150,000	161,300	176,500	191,600
	2,000L	55,700	63,300	71,000	79,200	87,100	95,500	103,900	112,600	123,900	135,100
	1,000L	29,900	33,700	37,500	41,600	45,500	49,800	53,900	58,400	64,300	70,000
	内900R×90°	63,600	70,600	77,300	84,200	91,500	98,600	106,000	113,600	125,000	136,300
150P	3,000L	66,300	73,900	81,900	90,300	98,300	106,500	114,500	122,600	134,000	145,200
	2,000L	41,900	47,400	52,900	58,600	64,400	70,100	76,200	82,300	90,400	98,400
	1,000L	22,800	25,600	28,700	31,900	34,900	38,400	41,400	44,700	49,200	53,600
	内900R×90°	54,700	59,900	65,500	71,000	76,700	82,400	88,500	93,500	102,900	112,300
200P	3,000L	56,000	61,900	67,800	73,700	79,900	86,600	93,200	99,500	108,400	117,500
	2,000L	36,500	40,500	44,700	48,900	53,300	57,700	62,300	66,900	73,600	80,300
	1,000L	20,000	22,100	24,300	26,400	28,700	30,800	33,200	35,500	39,000	42,600
	内900R×90°	50,300	54,800	59,400	64,000	68,700	73,400	78,300	83,200	91,600	100,000
ローラ単品	軸付	2,590	3,010	3,400	3,880	4,330	4,630	5,290	5,780	6,360	6,960
	軸なし	2,260	2,540	2,820	3,120	3,430	3,600	4,100	4,440	4,890	5,330

空圧・油圧・真空

直動システム・関連

ロボット・FA

制御・検出・計測

駆動・回転

軸受・素材・機械

動力伝達・伝動

搬送・運搬

ポンプ・送風機粉体

工場設備・環境