



## ボールベアリング外メタル式車輪 1台分2軸4輪 対法および価格

単位: mm

呼称No.	価格	車径	軸径	レールゲージ	ベアリングNo	取付芯々	1台当り積荷重kg
BB-107	190,190	305A	50	1,067	1,307	1,279	2,000
108	178,850	305A	50	510	1,308	728	3,000
109	183,460	305A	50	610	1,308	828	
110	188,080	305A	50	762	1,308	980	
111	210,000	305A	50	1,067	1,308	1,285	
112	196,730	305幅広	50	510	1,308	734	
113	200,580	305幅広	50	610	1,308	834	
114	205,380	305幅広	50	762	1,308	986	
115	226,540	305幅広	50	1,067	1,308	1,291	
116	219,620	305幅広	55	510	1,309	738	3,500
117	223,650	305幅広	55	610	1,309	838	
118	231,730	305幅広	55	762	1,309	990	
119	254,040	305幅広	55	1,067	1,309	1,295	
120	257,690	305丸B	60	510	1,309	738	
121	266,730	305丸B	60	610	1,309	838	
122	276,730	305丸B	60	762	1,309	990	
123	302,880	305丸B	60	1,067	1,309	1,295	
124	273,850	305丸B	60	510	1,310	748	5,000
125	285,190	305丸B	60	610	1,310	848	
126	296,920	305丸B	60	762	1,310	1,000	
127	321,730	305丸B	60	1,067	1,310	1,305	
128	306,920	305丸B	70	510	1,311	750	
129	317,120	305丸B	70	610	1,311	850	
130	329,230	305丸B	70	762	1,311	1,002	
131	356,540	305丸B	70	1,067	1,311	1,307	
132	405,190	305丸A	80	510	1,312	826	8,000
133	417,120	305丸A	80	610	1,312	926	
134	433,650	305丸A	80	762	1,312	1,078	
135	459,420	305丸A	80	1,067	1,312	1,384	
136	459,420	305丸A	80	510	1,313	827	
137	475,000	305丸A	80	610	1,313	927	
138	495,380	305丸A	80	762	1,313	1,079	
139	520,960	305丸A	80	1,067	1,313	1,384	
140	636,920	305丸Aボス大	100	510	1,316	852	14,000
141	650,770	305丸Aボス大	100	610	1,316	952	
142	676,150	305丸Aボス大	100	762	1,316	1,104	
143	713,650	305丸Aボス大	100	1,067	1,316	1,409	
144	243,080	355	50	510	1,308	773	
145	247,310	355	50	610	1,308	873	
146	253,080	355	50	762	1,308	1,025	
147	274,620	355	50	1,067	1,308	1,330	
148	266,540	355	55	510	1,309	777	4,000
149	271,920	355	55	610	1,309	877	
150	279,810	355	55	762	1,309	1,029	
151	302,690	355	55	1,067	1,309	1,334	
152	699,620	355丸Aボス大	100	510	1,316	852	
153	720,580	355丸Aボス大	100	610	1,316	952	
154	753,460	355丸Aボス大	100	762	1,316	1,104	
155	802,310	355丸Aボス大	100	1,067	1,316	1,409	
156	1,000,000	400丸A	110	610	22,217	958	20,000
157	1,034,600	400丸A	110	762	22,217	1,110	
158	1,098,000	400丸A	110	1,067	22,217	1,415	

呼称No.	価格	車径	軸径	レールゲージ	ベアリングNo.	取付芯々	1台当り積荷重kg	
BB-159	1,400,000	450丸A	130	610	22,220	974	30,000	
160	1,451,900	450丸A	130	762	22,220	1,126		
161	1,555,800	450丸A	130	1,067	22,220	1,431		
162	2,063,500	500丸A	150	610	22,224	1,015	40,000	
163	2,128,800	500丸A	150	762	22,224	1,167		
164	2,257,700	500丸A	150	1,067	22,224	1,472		
201	136,150	127A	50	510	1,307	710		約2,000
202	139,230	127A	50	610	1,307	810		
203	143,460	127A	50	762	1,307	962		
204	160,960	127A	50	1,067	1,307	1,267		
205	177,690	178A	50	510	1,308	716	3,000	
206	181,730	178A	50	610	1,308	816		
207	185,770	178A	50	762	1,308	968		
208	198,850	178A	50	1,067	1,308	1,273		
209	186,350	203A	50	510	1,308	724		3,000
210	189,810	203A	50	610	1,308	824		
211	194,620	203A	50	762	1,308	976		
212	208,850	203A	50	1,067	1,308	1,280		
213	219,810	230A	55	510	1,309	730	4,000	
214	223,650	230A	55	610	1,309	830		
215	231,730	230A	55	762	1,309	982		
216	254,040	230A	55	1,067	1,309	1,287		
217	167,120	255肉厚	44	510	1,307	716		2,000
218	151,540	255肉厚	44	610	1,307	816		
219	154,620	255肉厚	44	762	1,307	968		
220	183,270	255肉厚	44	1,067	1,307	1,273		
221	250,380	255特B	55	510	1,309	748	4,000	
222	256,540	255特B	55	610	1,309	848		
223	262,880	255特B	55	762	1,309	1,000		
224	285,960	255特B	55	1,067	1,309	1,305		
225	268,650	250特A	60	510	1,310	760		5,000
226	279,810	250特A	60	610	1,310	860		
227	291,540	250特A	60	762	1,310	1,012		
228	317,120	250特A	60	1,067	1,310	1,317		
229	261,920	355B	55	510	1,309	760	4,000	
230	268,080	355B	55	610	1,309	860		
231	275,770	355B	55	762	1,309	1,012		
232	297,690	355B	55	1,067	1,309	1,317		
233	527,120	355A	90	510	1,314	810		12,000
234	541,150	355A	90	610	1,314	910		
235	563,460	355A	90	762	1,314	1,062		
236	587,690	355A	90	1,067	1,314	1,367		
237	757,500	400丸B	100	610	1,315	950	14,000	
238	777,500	400丸B	100	762	1,315	1,102		
239	817,880	400丸B	100	1,067	1,315	1,407		
240	878,460	450丸B	100	610	1,316	964		16,000
241	898,650	450丸B	100	762	1,316	1,116		
242	940,960	450丸B	100	1,067	1,316	1,421		
243	1,050,000	500丸B	110	610	22,217	968	20,000	
244	1,074,200	500丸B	110	762	22,217	1,120		
245	1,122,700	500丸B	110	1,067	22,217	1,425		

呼称No.01～40迄車輪の材質は普通鑄鉄製で外径にチルドが入れてありません。No.41～155迄は、すべて外径(車径)部分にチルド(冷剛硬化)シヨアー硬度60以上をほどこしてあり、No.156～164迄はダクタイルチルド車輪を使用しております。尚、積載重量は1台分(2軸4輪)に対する安全積載量です。BB245をこえるの形番についてはNKS専用カタログを参照願います。

空圧・油圧・真空

直動システム・閉連

ロボット・F/A

制御・検出・計測

駆動・回転

軸受・素材・機械

動力伝達・伝動

搬送・運搬

ポンプ・送風機粉体

工場設備・環境