

油圧式テーブルリフト

(株)スギヤス

312961

耐久性抜群、全58機種
全シリーズ押ボタンスイッチ付

1TONシリーズ標準仕様および価格

電源：三相200V

型 式	価 格	能力 (kg)	テーブル寸法 (mm)					モーター (kW)	揚速 (秒)		自重 (kg)	油圧ユニット			
			幅	長さ	最低高	最高高	ストローク		50Hz	60Hz					
X10410-B	396,000	1000	400	1000	155	755	600	0.75	13	11	163	別置			
X10413-B	412,000			1340		1000	845		24	20	210				
X10415-B	427,000			1500	205	950	24		20	248					
2X10607-B	567,000		600	780	255	1155	900	0.55	33	28	226	内蔵			
2AX100AP-B2	823,000								800	1214	960		14	12	219
2AX100AR-B2	871,000				950	1394	1140		21	18	259				
2X10610-B	598,000			640	1000	255	1505	1250	0.55	45	38	250	内蔵		
2X10611-B	613,000									1150	1655	1400		28	23
2AX100AS-B2	910,000					254	1634	1380		27	23	314			
2X10614-B	660,000				780	1400	306	2106	1800	1.13	34	28	370	別置	
2X10618-B	784,000	1850									2756	2400	66		55
NX100NA-B	334,000	850					555	400	10		8	161			
NX100NB-B	348,000	850				1000	155	755	600	0.7	13	11	175	内蔵	
NX100NC-B	374,000		1340								1000	845	24		20
NX100ND-B	393,000		1500				205	1155	950		17	14	248		
NX100NE-B	429,000		1800			1510	1305	25	21	313					
AX100VJ-B	734,000		900	2000		270	1470	1200	1.13	43	36	417	内蔵		
NX100WA-B	343,000									850	555	400		10	8
NX100WB-B	360,000					1000	155	755		600	13	11		194	
NX100WC-B	384,000			850	1340	155	1000	845	0.7	24	20	244	内蔵		
NX100WD-B	402,000									1500	1155	950		17	14
NX100WE-B	447,000					1800	205	1510		1305	25	21		335	
2X10910-B	614,000	1000			1000	255	1505	1250	1.13	24	20	330	内蔵		
2X10911-B	645,000									1150	1655	1400		28	23
2X10914-B	691,000					1400	306	2106		1800	34	28		400	
2X10918-B	814,000				900	1850	356	2756	2400	1.5	49	41	726	内蔵	
2AX100BR-B2	903,000		950								1394	1140	22		19
2AX100BS-B2	953,000		1150				1634	1380	30		25	384			
2AX100BT-B2	999,000		1000			1380	254	1904	1650	2.2	35	30	465	内蔵	
2AX100BV-B2	1,045,000			1670							2254	2000	43		36
AX100XJ-B	750,000			2000			270	1470	1200		24	20	481		
AX100RF-B	618,000			1000		1000	270	770	500	0.7	15	13	281	内蔵	
NX100WCY-B	410,000	1340									155	1000	845		24
AX100RG-B	662,000	270					1070	800	22		18	327			
NX100WDY-B	424,000	1200				155	205	1155	950	1.13	17	14	281	内蔵	
AX100RH-B	713,000				270						1170	900	0.7		25
AX100RI-B	786,000				1800		270	1350	1080		0.7	33	28		426
NX100WEY-B	471,000				1250	2000	205	1510	1305	1.13	25	21	357	内蔵	
2X11211-B	691,000		1150								255	1655	1400		28
2AX100CT-B2	1,201,000		1380				254	1904	1650		2.2	35	30		573
2X11214-B	814,000		1300			1400	306	2106	1800	1.13	34	28	595	内蔵	
2AX100CV-B2	1,321,000			1670							254	2254	2000		2.2
2X11218-B	938,000			1850			356	2756	2400		1.5	49	41		827
2AX100CW-B2	1,447,000			1500		2000	350	2750	2400	2.2	58	49	825	内蔵	
X11224-B	500,000	2400									207	1512	1305		1.13
AX100SH-B	773,000	1500					270	1170	900		0.7	30	25		448
AX100SI-B	819,000	1500				1800	270	1350	1080	0.7	37	31	513	内蔵	
AX100YJ-B	794,000				270						1470	1200	1.5		24
AX100ZJ-B	832,000				270		1470	1200	1.5		24	20	578		



X10410-B



NX100WC-B



2X11214-B



2AX100BS-B



足踏スイッチ(オプション)

別置油圧ユニット寸法

型 式	寸法 L×W×H (mm)	高压ホース
X10410	430×361×247	約3m
X10413		
X10415		
2AX100AP	550×400×300	
2AX100AR		
2AX100AS		

高压ホース長はテーブル寸法の高さによって変わります。

空圧・油圧・真空

直動システム・関連

ロボット・FA

制御検出・計測

駆動・回転

軸受・素材・機械

動力伝達・伝動

搬送・運搬

ポンプ・送風機・粉体

工場設備・環境