

三菱 有圧換気扇

三菱電機(株)

403471

有圧換気扇仕様

電源について3相 :200V、3相 :200V-220V、3相 :200/200/220V(50/60/60Hz)

タイプ	羽根径 (cm)	形名	価格	電源	極数 (P)	公称出力 (W)	50Hz				60Hz				質量 (kg)	給気使用可否		
							風量 (m³/h)	騒音 (dB)	電流 (A)	消費電力 (W)	風量 (m³/h)	騒音 (dB)	電流 (A)	消費電力 (W)				
低騒音形 エクストラグレード (給気タイプ)	45	EF-45ESB ₂ -Q	80,600	単相100V 3相	4	400	5400	59	2.50	245	6300	63.5	3.70	360	19.4	排気使用不可		
		EF-45ETB ₂ -Q	80,600				5640	59.5	1.30-1.39	235-245	6600	64	1.35-1.37	340-350	17.8			
		EG-45DSB-Q	73,600				53	2.09	190	57	2.63	263	18.4					
	50	EG-45DTB ₁ -Q	73,600	3相	6	200	4500	52.5-53	1.10-1.20	178-190	5280	57.5	1.07-1.11	240-250	19.8			
		EF-50FTB ₁ -Q	87,800				6900	63-63.5	1.48-1.54	347-368	8280	67.5-68	1.86-1.81	537-550	26.2			
		EG-50DTB-Q	71,000				200	4800	52	1.13-1.32	162-189	5640	56.5-57	1.00-1.07	204-212		16.5	
		EG-50ETB ₁ -Q	81,800				400	6060	56-56.5	1.85-2.08	254-280	7140	61-61.5	1.67-1.80	332-356		19.7	
	60	EG-60ETB ₁ -Q	91,100	3相	6	750	7860	56.5-57	1.32-1.43	235-251	9210	61-61.5	1.37-1.41	332-352	22			
		EG-60FTB ₁ -Q	109,000				9420	61	1.91-2.00	406-419	11160	65.5-67	2.29-2.23	620-633	27.3			
		KG-70GTF ₂	169,000				1500	17100	64.5	5.6	800	20400	68	5.3/5.5	1130/1200		52	
大風量形 エクストラグレード (排気タイプ)	25	KG-80HTF ₁	198,000	3相	6	2200	23100	69	5.8	1060	27000	73	6.3/6.3	1600/1670	62.5	可		
		EF-25ATB40A ₃	28,800				25	1140	36.5	0.09/0.10	32/36	1320	39.5	0.09/0.10	42/45		3.9	
	30	EF-30BTB40A ₃	37,200	3相	4	50	1680	41	0.20/0.22	64/72	1980	45	0.19/0.20	78/85	5.4			
		EF-35CTB40A ₃	49,500				100	2400	46	0.32/0.37	90/102	2880	49.5	0.29/0.32	108/118		6.6	
	35	EF-35DTB40A ₃	54,500	3相	4	150	3000	47	0.50/0.58	125/140	3600	51	0.46/0.50	173/180	9.4			
		EF-40DTB40A ₃	62,500				200	3720	48	0.50/0.55	130/140	4320	51	0.48/0.52	180/187		11.2	
	40	EF-40ETB40A ₄	70,000	3相	4	400	4800	51.5	0.60/0.64	230/243	5520	55.5	0.68	348/358	13.4			
		EF-50FTB40A ₃	87,800				750	6900	54.5	0.72/0.74	320/325	8280	58.5	0.87	500/510		25.2	
	60	EG-60FTB40A ₃	109,000	3相	6	750	9420	52.5	1.10/1.15	390/420	11160	56.5	1.25	620/640	26.3			
		EF-25ATB40A ₃ -Q	31,700				25	1140	43	0.09/0.10	32/35	1320	47	0.09	42/45		4.3	
400V級低騒音形 エクストラグレード (給気タイプ)	25	EF-30BTB40A ₃ -Q	40,900	3相	4	50	1680	48.5	0.16/0.17	59/63	1980	51.5	0.16/0.17	73/80	5.8	否		
		EF-35CTB40A ₃ -Q	54,500				100	2400	51.5	0.24/0.26	82/92	2880	55/56	0.24/0.25	110/118		7.3	
	35	ET-35DTB40A ₃ -Q	60,000	3相	4	150	3000	54.5	0.49/0.58	123/138	3600	59	0.45/0.49	172/180	10.3			
		EF-40DTB40A ₃ -Q	68,800				200	3720	57	0.50/0.55	135/145	4320	61/61.5	0.49/0.52	190/205		12.3	
	40	EF-40ETB40A ₁ -Q	77,000	3相	4	400	4800	58.5	0.62/0.68	235/255	5520	63.5	0.68/0.70	360/365	14.2			
		EF-50FTB40A ₃ -Q	96,600				750	6900	62.5	0.76/0.78	345/360	8280	66.5	0.95/0.92	555/560		26.2	
	60	EG-60FTB40A ₃ -Q	119,900	3相	6	750	9420	59	1.15/1.20	435/445	11160	64	1.30	660/680	27.3			
		EF-40ETB ₁ -PR	115,000				4	400	4800	51.5	1.1	225	5520	55.5	1.25/1.25		340/350	14.1
	防錆タイプ	50	EF-50FTB-PR	144,000	3相	4	750	6900	54.5	1.45	340	8280	59	1.8/1.75	530/540		26.1	否
			EG-50ETB-PR	134,000				6	400	6060	48	2.35	285	7140	51.5		2.0/1.27	
60		EG-60ETB-PR	149,000	3相	6	400	7860	50.5	2.1	295	9210	54.5	1.9/2.0	385/410	21.1			
		EG-60FTB-PR	178,000				750	9420	53	1.85	401	11160	57.5	2.2/2.2	585/600	27.3		
大風量形		KG-70GTF ₂ -PR	305,000	3相	6	1500	16900	64.5	5.6	800	19700	68	5.3/5.5	1130/1200	52			
		KG-80HTF ₁ -PR	357,000				6	2200	23100	69	5.8	1060	27000	73	6.3/6.3	1600/1670	62.5	
ステンレスタイプ		20	EF-20YSXB	85,500	単相100V	4	15	660	32.5	0.32	30.5	780	36.5	0.32	32	3.6	可	
			EF-25ASXB	86,800				4	25	1080	37.5	0.56	41	1260	40.5	0.47		
		25	EF-25ATXB	86,800	3相	4	50	1680	39.5	0.31	42	1980	43	0.25/0.28	44/48	6.5		
			EF-30BSXB	117,000				4	50	1680	39.5	0.59	53	1980	43	0.71		
	30	EF-30BTXB	117,000	3相	4	200	3760	49.5	0.3	50.5	4360	53.5	0.28/0.31	60/65	15			
		EF-40DSXB	146,000				4	200	3760	49.5	2.1	148	4360	53.5	2.1	198		13.5
	40	EF-40DTXB	146,000	3相	6	100	3060	41	0.82	135	3660	44	0.8/0.83	185/190	16			
		EG-40CSXB	140,000				6	400	6060	48	1.36	104	11160	57.5	1.31	126		16
	50	EG-40CTXB	140,000	3相	6	750	9420	53	0.7	101	11160	44	0.63/0.7	119/130	14.9			
		EG-50ETXB	260,000				6	400	6060	48	1.3	200	7140	51.5	1.30/1.33	280/290		27
60	EG-60FTXB	343,000	3相	6	750	9420	53	3.0	420	11160	57.5	2.9/3.0	590/610	33				
	EF-30BSXB-F	153,000				4	50	1680	39.5	0.59	53	1980	43	0.71	70	6.5		
防爆形 エクストラグレード	30	EF-30BTXB-F	153,000	単相100V	4	200	3760	49.5	0.3	50.5	4360	53.5	0.28/0.31	60/65	15	可		
		EF-40DSXB-F	190,000				4	200	3760	49.5	2.1	148	4360	53.5	2.1		198	15
	40	EF-40DTXB-F	190,000	3相	6	400	6060	48	0.82	135	7140	51.5	0.80/0.83	185/190	13.5			
		EG-50ETXB-F	482,000				6	400	6060	48	1.3	200	7140	51.5	1.30/1.33		280/290	27
	60	EG-60FTXB-F	636,000	3相	6	750	9420	53	3.0	420	11160	57.5	2.9/3.0	590/610	33			
		EF-20YSD-V	86,100				4	15	670	33	0.41	27	790	36	0.30		27	6.5
	25	EF-25ASD-V	91,400	単相100V	4	25	1170	37	0.44	35	1380	40	0.47	42	6.9			
		EF-30BSD-V	118,000				4	50	1700	39	0.62	61	1980	42	0.78		77	7.5
	30	EF-30BD-V	118,000	3相	4	200	3860	46	0.24	47	4470	50	0.26	63	21.6			
		EF-40DTC-V	141,000				6	200	4960	44	1.04	142	5760	47.5	0.68		178	26.8
40	EG-50DTC-V	175,000	3相	6	200	4960	44	1.04	142	5760	47.5	0.94	180	26.8				
	EG-60FTC-V	294,000				6	750	10100	52.5	3.5	475	12000	56.5	3.3	660	48.8		
機器冷却用	25	EF-25US	27,200	単相100V	4	25	1140	38	0.46	45	1320	42	0.55	54	3.8	否		
		EF-25USS	27,200				860	41	0.46	45	970	45	0.56	56	3.8			
	30	EF-25US-K	42,900	3相	4	50	1140	40	0.46	45	1320	44	0.55	54	4.2			
		EF-25USS-K	42,900				860	44	0.46	45	970	48	0.56	56	4.2			
	40	EF-30US	34,800	3相	4	50	1680	42	0.6	56	1980	45.5	0.72	69	4.6			
		EF-30USS	34,800				1490	46	0.72	60	1670	50	0.72	68	4.9			
	50	EF-30US-K	49,400	3相	6	1950	1680	43.5	0.6	58	1950	46	0.72	71	5			
		EF-30USS-K	49,400				1490	48	0.72	60	1670	51.5	0.72	68	5.3			
	耐熱タイプ	40	EF-40ETB ₂ -H	122,000	3相	4	400	4800	51.5	1.10-1.15	230-245	5520	55.5	1.28	345-355		15	
		50	EF-50FTB ₁ -H	153,000				4	750	6900	55	1.45-1.50	330-345	8280	59-59.5		1.70-1.65	512-520
60		EG-60FTB ₁ -H	189,000	6				750	9420	52	2.10-2.20	410-420	11160	56	2.5	595-615	28.8	
冷凍室タイプ	40	EF-40DRA	109,000	3相	4	200	3400	47	0.48	110	3900	51	0.57	160	12.5	否		
	50	EF-50ERA	142,000				4	400	5800	54	1.70	280	6800	58	1.60		400	18.0
	60	EG-60FRA	189,000				6	750	9140	53	1.80	365	10800	57	2.10		560	27.3

印は受注生産品(納期2か月)です。

空圧・油圧・真空
直動システム・関連
制御・検出・計測
駆動・回転
軸受・素材・機械
動力伝達・伝動
搬送・運搬
ポンプ・送風機・粉体
工場設備・環境